



ProKlean Multi-Purpose Cleaner

MPC1;MPC5

SDS Revision Date (mm/dd/yyyy): 04/13/2015

Page 1 of 12

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: **ProKlean Multi-Purpose Cleaner**

Product Code(s) : MPC1 (P/N 475158); MPC5 (P/N 475162)

Recommended use of the chemical and restrictions on use

: Professional Use Only: Refrigeration coil cleaner

Chemical family : Mixture.

Name, address, and telephone number of the supplier:

Parker Hannifin Corporation - Sporlan Division

206 Lange Drive
Washington, MO, U.S.A.
63090

Supplier's Telephone # : (636)-239-1111

24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887 (Outside U.S.).

Name, address, and telephone number of the manufacturer:

Refer to supplier

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

WHMIS information: This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Canadian Controlled Products Regulations (CPR). WHMIS classification:
Class E (Corrosive Material)

OSHA: This material is classified as hazardous under OSHA regulations (29CFR 1910.1200) (Hazcom 2012). OSHA Classification:

Corrosive to metals: Category 1
Eye damage/irritation: Category 1
Skin corrosion/irritation: Category 1
Specific target organ toxicity - single exposure Category 3

Label elements

The following label information is applicable only to the United States according to OSHA Regulations (29 CFR 1910.1200) (Hazcom 2012):

Signal Word

DANGER!

Hazard statement(s)

May be corrosive to metals.
Causes severe skin burns and eye damage.
May cause respiratory irritation.



ProKlean Multi-Purpose Cleaner

MPC1;MPC5

SDS Revision Date (mm/dd/yyyy): 04/13/2015

Page 2 of 12

SAFETY DATA SHEET

Precautionary statement(s)

Keep only in original container.
Wash thoroughly after handling.
Do not breathe mists.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/clothing and eye/face protection.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Do NOT induce vomiting.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
Wash contaminated clothing before reuse.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a POISON CENTER or doctor/physician.
Absorb spillage to prevent material damage.

Store in corrosive resistant container with a resistant inner liner.
Store locked up.
Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.



The following label information is applicable only to Canada according to the Canadian Controlled Products Regulations (CPR/WHMIS):

DANGER!

May be corrosive to metals. Contact with metals may release small amounts of flammable hydrogen gas. Corrosive material. May cause severe burns to all routes of exposure. May cause severe irritation to the nose, throat and respiratory tract.

Use in a well-ventilated area. Wear protective gloves/clothing and eye/face protection. Do not ingest. Do not breathe vapours or spray mist. Keep away from bases, metals and other incompatibles. Keep containers tightly closed when not in use. Wash thoroughly after handling.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If breathing stopped, begin artificial respiration. If breathing is difficult, administer oxygen. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTRE or doctor/physician.



Other hazards

Other hazards which do not result in classification:

Ingestion may cause severe irritation to the mouth, throat and stomach. Contact with metals may release small amounts of flammable hydrogen gas. Prolonged skin contact may cause dermatitis (rash), characterized by red, dry, itching skin. May cause respiratory tract irritation.



ProKlean Multi-Purpose Cleaner

MPC1;MPC5

SDS Revision Date (mm/dd/yyyy): 04/13/2015

Page 3 of 12

SAFETY DATA SHEET

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical name</u>	<u>CAS #</u>	<u>Concentration</u>
Sodium metasilicate	6834-92-0	37.0 - 0.0
Tall oil fatty acids	61790-12-3	1.0 - 5.0
Alcohols, C9-11, ethoxylated	68439-46-3	1.0 - 5.0
Potassium hydroxide	1310-58-3	1.0 - 3.0
Sodium xylene sulphonate	1300-72-7	1.0 - 3.0

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : Do NOT induce vomiting. Have victim rinse mouth with water, then give one to two glasses of water to drink. Seek immediate medical attention/advice. Never give anything by mouth if victim is unconscious.
- Inhalation* : Immediately remove person to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Seek immediate medical attention/advice.
- Skin contact* : Take off all contaminated clothing immediately. Immediately flush skin with gently flowing, running water for at least 20 minutes. Do not rub area of contact. Seek immediate medical attention/advice. Wash contaminated clothing before reuse.
- Eye contact* : Immediately flush eyes with running water for at least 20 minutes. Seek immediate medical attention/advice.

Most important symptoms and effects, both acute and delayed

- : May cause serious eye irritation or damage. Symptoms may include redness, pain, tearing and conjunctivitis. Direct skin contact may cause corrosive skin burns, deep ulcerations and possibly permanent scarring. May cause severe irritation and corrosive damage in the mouth, throat and stomach. Symptoms may include abdominal pain, vomiting, burns, perforations, bleeding and eventually death. May cause severe irritation to the nose, throat and respiratory tract. Symptoms may include coughing, choking and wheezing. Could result in pulmonary edema (fluid accumulation). Symptoms of pulmonary edema (chest pain, shortness of breath) may be delayed.

Indication of any immediate medical attention and special treatment needed

- : Immediate medical attention is required. Causes burns. Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

- Suitable extinguishing media* : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

- Unsuitable extinguishing media* : Do not use direct stream of water, which can result in a dust cloud and explosion hazard.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Not considered flammable. Burning produces obnoxious and toxic fumes.

Flammability classification (OSHA 29 CFR 1910.106)

- : Non-flammable.

Explosion Data: Sensitivity to Mechanical Impact / Static Discharge:

- : Not expected to be sensitive to mechanical impact or static discharge.



ProKlean Multi-Purpose Cleaner

MPC1;MPC5

SDS Revision Date (mm/dd/yyyy): 04/13/2015

Page 4 of 12

SAFETY DATA SHEET

Hazardous combustion products

- : Carbon dioxide and carbon monoxide. Aldehydes Sodium oxides Silicon oxides. Hydrogen sulfur oxides

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

- : Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire-fighting procedures

- : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. A full-body chemical resistant suit should be worn. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. Dike for water control. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up. Refer to Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.

Environmental precautions

- : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. For large spills, dike the area to prevent spreading.

Methods and material for containment and cleaning up

- : Remove all sources of ignition. Ventilate area of release. Stop spill or leak at source if safely possible. Dike for water control. Recovered solutions can be carefully diluted with water and then neutralized with acids, such as acetic acid (vinegar) or hydrochloric acid. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13).

Special spill response procedures

- : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).
US CERCLA Reportable quantity (RQ): Potassium hydroxide (1000 lbs / 454 kg)

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

- : Use in a well-ventilated area. Wear chemically resistant protective equipment during handling. See Section 8 for additional personal protection advice when handling this product. Do not ingest. Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Keep away from extreme heat and flame. Keep away from bases, metals and other incompatibles. Keep container tightly closed when not in use. Wash thoroughly after handling.

Conditions for safe storage

- : Store in a cool, dry, well-ventilated area. Store away from incompatibles and out of direct sunlight. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. Store in corrosion-resistant containers. After prolonged storage, may release explosive peroxides in the presence of air. Rate of peroxide formation is not known. Direct sunlight or heat may accelerate the release of peroxides.

Incompatible materials

- : Acids; Strong oxidizing agents; Metals (e.g. Aluminum, brass, copper).

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION



SAFETY DATA SHEET

<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Sodium metasilicate	N/Av	N/Av	N/Av	N/Av
Tall oil fatty acids	N/Av	N/Av	N/Av	N/Av
Alcohols, C9-11, ethoxylated	N/Av	N/Av	N/Av	N/Av
Potassium hydroxide	N/Av	N/Av	N/Av	N/Av
Sodium xylene sulphonate	N/Av	N/Av	N/Av	N/Av

Exposure controls

Ventilation and engineering measures

: Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.

Respiratory protection

: If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Confirmation of which type of respirator is most suitable for the intended application should be obtained from respiratory protection suppliers. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

Skin protection

: Wear chemically protective gloves (impervious), boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear impervious gloves, such as butyl rubber. Unsuitable material: polyvinyl alcohol. Advice should be sought from glove suppliers.

Eye / face protection

: Chemical splash goggles must be worn when handling this material. A full face shield may also be necessary.

Other protective equipment

: Other equipment may be required depending on workplace standards. An eyewash station and safety shower should be made available in the immediate working area.

General hygiene considerations

: Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove and wash contaminated clothing before re-use. Do not take contaminated clothing home.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Clear liquid.
Odour	: Bland odor.
Odour threshold	: N/Av
pH	: >12.5
Melting/Freezing point	: 0°C (32°F)
Initial boiling point and boiling range	: 100°C (212°F)
Flash point	: >100 °C (>212°F)
Flashpoint (Method)	: Setaflash Closed Tester
Evaporation rate (BuAe = 1)	: >1
Flammability (solid, gas)	: Not applicable.
Lower flammable limit (% by vol.)	: N/Av
Upper flammable limit (% by vol.)	: N/Av



ProKlean Multi-Purpose Cleaner

MPC1;MPC5

SDS Revision Date (mm/dd/yyyy): 04/13/2015

Page 6 of 12

SAFETY DATA SHEET

Oxidizing properties : None known.

Explosive properties : Not explosive

Vapour pressure : 12.4

Vapour density : 0.4

Relative density / Specific gravity

: 1.12

Solubility in water : soluble

Other solubility(ies) : None known.

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: N/Av

Auto-ignition temperature : N/Ap

Decomposition temperature : Not available.

Viscosity : < 10 cps

Volatiles (% by weight) : 88.3% (Water)

Volatile organic Compounds (VOC's)

: 0

Absolute pressure of container

: N/Ap

Flame projection length : N/Ap

Other physical/chemical comments

: None.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive. Contact with metals may release small amounts of flammable hydrogen gas. Corrosive in contact with metals After prolonged storage, may release explosive peroxides in the presence of air. Rate of peroxide formation is not known. Direct sunlight or heat may accelerate the release of peroxides.

Chemical stability : Stable under the recommended storage and handling conditions prescribed.

Possibility of hazardous reactions

: Hazardous polymerization does not occur. Contact with metals may release small amounts of flammable hydrogen gas.

Conditions to avoid : Avoid heat and open flame. Ensure adequate ventilation, especially in confined areas. Avoid contact with incompatible materials. Keep out of direct sunlight.

Incompatible materials : Acids; Strong oxidizing agents;Metals (e.g. Aluminum, brass, copper).

Hazardous decomposition products

: Peroxides. Refer also to hazardous combustion products, Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES

Routes of entry skin & eye : YES

Routes of entry Ingestion : YES

Routes of exposure skin absorption

: NO



ProKlean Multi-Purpose Cleaner

MPC1;MPC5

SDS Revision Date (mm/dd/yyyy): 04/13/2015

Page 7 of 12

SAFETY DATA SHEET

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

- : Inhalation of high concentrations of fumes or mists may cause severe irritation and corrosive damage to the nose, throat and upper respiratory tract. Symptoms may include coughing, choking and wheezing. Could result in pulmonary edema (fluid accumulation). Symptoms of pulmonary edema (chest pain, shortness of breath) may be delayed.

Sign and symptoms ingestion

- : May cause severe irritation and corrosive damage in the mouth, throat and stomach. Symptoms may include abdominal pain, vomiting, burns, perforations, bleeding and eventually death.

Sign and symptoms skin

- : This material is classified as hazardous under OSHA regulations (29CFR 1910.1200) (Hazcom 2012). Classification: Skin corrosion/irritation: Category 1
Causes severe skin burns and eye damage. Direct skin contact may cause corrosive skin burns, deep ulcerations and possibly permanent scarring.

Sign and symptoms eyes

- : This material is classified as hazardous under OSHA regulations (29CFR 1910.1200) (Hazcom 2012). Classification: Eye damage/irritation: Category 1
Causes serious eye damage.

Potential Chronic Health Effects

- : Chronic skin contact with low concentrations may cause dermatitis.

Mutagenicity

- : Not expected to be mutagenic in humans.

Carcinogenicity

- : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects & Teratogenicity

- : Not expected to cause reproductive effects.

Senitization to material

- : Not expected to be a skin or respiratory sensitizer.

Specific target organ effects

- : Target Organs: Eyes, skin, respiratory system and digestive system.

This material is classified as hazardous under OSHA regulations (29CFR 1910.1200) (Hazcom 2012). Classification:
Specific target organ toxicity - single exposure -Category 3
May cause respiratory irritation.

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Irritancy

- : Corrosive.

Medical conditions aggravated by overexposure

- : Pre-existing skin, eye and respiratory disorders.

Synergistic materials

- : Not available.

Toxicological data

- : See below for individual ingredient acute toxicity data.



ProKlean Multi-Purpose Cleaner

MPC1;MPC5

SDS Revision Date (mm/dd/yyyy): 04/13/2015

Page 8 of 12

SAFETY DATA SHEET

<u>Chemical name</u>	<u>LC₅₀(4hr)</u>	<u>LD₅₀</u>	
	<u>inh, rat</u>	<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Sodium metasilicate	>2.06 mg/L (no deaths)	1152-1349 mg/kg	>5000mg/kg
Tall oil fatty acids	n/av	>10,000 mg/kg	>2000 mg/kg
Alcohols, C9-11, ethoxylated	N/Av	1378 mg/kg	>2000 mg/kg
Potassium hydroxide	N/Av	250 mg/kg	> 1260 mg/kg
Sodium xylene sulphonate	N/Av	7200 mg/kg	N/Av

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity : The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters. Harmful to aquatic life.

Ecotoxicity data:

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Fish</u>		
		<u>LC50 / 96h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
Sodium metasilicate	6834-92-0	260-310mg/L (Rainbow trout)	N/Av	None.
Tall oil fatty acids	61790-12-3	>1000mg/L (Fathead minnow)	N/Av	None.
Alcohols, C9-11, ethoxylated	68439-46-3	8.5 mg/L (Fathead minnow)	N/Av	None.
Potassium hydroxide	1310-58-3	80 mg/L (Mosquito fish)	N/Av	None.
Sodium xylene sulphonate	1300-72-7	>400mg/L (Fathead minnow)	N/Av	None.

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Daphnia</u>		
		<u>EC50 / 48h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
Sodium metasilicate	6834-92-0	1700mg/L (Water flea)	N/Av	None.
Tall oil fatty acids	61790-12-3	>1000mg/L (Water flea)	N/Av	None.
Alcohols, C9-11, ethoxylated	68439-46-3	5.3 mg/L (Water flea)	N/Av	None.
Potassium hydroxide	1310-58-3	56 mg/L Ceriodaphnia (water flea)	N/Av	None.
Sodium xylene sulphonate	1300-72-7	>408mg/L (Water flea)	N/Av	None.



ProKlean Multi-Purpose Cleaner

MPC1;MPC5

SDS Revision Date (mm/dd/yyyy): 04/13/2015

Page 9 of 12

SAFETY DATA SHEET

Ingredients	CAS No	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
Sodium metasilicate	6834-92-0	>345 mg/L (Green algae)	160mg/L (Green algae)	None.
Tall oil fatty acids	61790-12-3	854.9 mg/L (Green algae)	>=1000 mg/L (Green algae)	None.
Alcohols, C9-11, ethoxylated	68439-46-3	N/Av	N/Av	None.
Potassium hydroxide	1310-58-3	N/Av	N/Av	None.
Sodium xylene sulphonate	1300-72-7	230mg/L (Green algae)	N/Av	None.

Persistence and degradability

: Biodegradation is not applicable to inorganic materials.

Bioaccumulation potential

: No data is available on the product itself.

Mobility in soil

: No data is available on the product itself.

Other Adverse Environmental effects

: No additional information.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

: Handle waste according to recommendations in Section 7. Empty containers retain residue (liquid and/or vapour) and can be dangerous.

Methods of Disposal

: Dispose in accordance with all applicable federal, state, provincial and local regulations.

RCRA

: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14. TRANSPORTATION INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1760	Corrosive liquid, n.o.s. (Potassium hydroxide, Sodium metasilicate)	8	III	
49CFR/DOT Additional information	RQ=(1000 lbs / 454 kg)				
TDG	UN1760	CORROSIVE LIQUID, N.O.S. (Potassium hydroxide, Sodium metasilicate)	8	III	
TDG Additional information					
ICAO/IATA	UN1760	Corrosive liquid, n.o.s. (Potassium hydroxide, Sodium metasilicate)	8	III	
ICAO/IATA Additional information					



ProKlean Multi-Purpose Cleaner

MPC1;MPC5

SDS Revision Date (mm/dd/yyyy): 04/13/2015

Page 10 of 12

SAFETY DATA SHEET

Special precautions for user : None known.
Environmental hazards : See ECOLOGICAL INFORMATION, Section 12.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
 : Not applicable.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

<u>Ingredients</u>	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de minimus Concentration
Sodium metasilicate	6834-92-0	Yes	N/Ap	N/Av	No	N/Ap
Tall oil fatty acids	61790-12-3	Yes	N/Ap	N/Ap	No	N/Ap
Alcohols, C9-11, ethoxylated	68439-46-3	Yes	N/Ap	N/Ap	No	N/Ap
Potassium hydroxide	1310-58-3	Yes	1000 lb/ 454 kg	None.	No	N/Ap
Sodium xylene sulphionate	1300-72-7	Yes	N/Ap	N/Av	No	N/Ap

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

<u>Ingredients</u>	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Sodium metasilicate	6834-92-0	No	N/Ap	No	No	No	No	No	No
Tall oil fatty acids	61790-12-3	No	N/Ap	No	No	No	No	No	No
Alcohols, C9-11, ethoxylated	68439-46-3	No	N/Ap	No	No	No	No	No	No
Potassium hydroxide	1310-58-3	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Sodium xylene sulphionate	1300-72-7	No	N/Ap	No	No	No	No	No	No

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.



ProKlean Multi-Purpose Cleaner

MPC1;MPC5

SDS Revision Date (mm/dd/yyyy): 04/13/2015

Page 11 of 12

SAFETY DATA SHEET

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	<u>CAS #</u>	<u>European EINECs</u>	<u>Australia AICS</u>	<u>Philippines PICCS</u>	<u>Japan ENCS</u>	<u>Korea KECI/KECL</u>	<u>China IECSC</u>	<u>NewZealand IOC</u>
Sodium metasilicate	6834-92-0	229-912-9	Present	Present	(1)-508	KE-12354	Present	HSR003511
Tall oil fatty acids	61790-12-3	263-107-3	Present	Present	(7)-972; (7)-978	KE-32785	Present	No information available.
Alcohols, C9-11, ethoxylated	68439-46-3	N/Av	Present	Present	(7)-97	KE-13383	Present	HSR003338; HSNO Approval: HSR006495 (dilution)
Potassium hydroxide	1310-58-3	215-181-3	Present	Present	(1)-369	KE-29139	Present	HSR001546
Sodium xylene sulphonate	1300-72-7	215-090-9	Present	Present	(3)-1909	KE-11217	Present	HSR003382

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists
 CA: California
 CAS: Chemical Abstract Services
 CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
 CFR: Code of Federal Regulations
 DOT: Department of Transportation
 EPA: Environmental Protection Agency
 HMIS: Hazardous Materials Identification System
 HSDB: Hazardous Substances Data Bank
 IARC: International Agency for Research on Cancer
 Inh: Inhalation
 IUCLID: International Uniform Chemical Information Database
 MA: Massachusetts
 MN: Minnesota
 MSHA: Mine Safety and Health Administration
 N/Av: Not Applicable
 N/Av: Not Available
 NFPA: National Fire Protection Association
 NIOSH: National Institute of Occupational Safety and Health
 NJ: New Jersey
 NTP: National Toxicology Program
 OSHA: Occupational Safety and Health Administration
 PA: Pennsylvania
 PEL: Permissible exposure limit
 RCRA: Resource Conservation and Recovery Act
 RI: Rhode Island
 RTECS: Registry of Toxic Effects of Chemical Substances
 SARA: Superfund Amendments and Reauthorization Act
 STEL: Short Term Exposure Limit
 TDG: Canadian Transportation of Dangerous Goods Act & Regulations
 TLV: Threshold Limit Values
 TWA: Time Weighted Average
 WHMIS: Workplace Hazardous Materials Identification System



ProKlean Multi-Purpose Cleaner

MPC1;MPC5

SDS Revision Date (mm/dd/yyyy): 04/13/2015

Page 12 of 12

SAFETY DATA SHEET

References : Canadian Centre for Occupational Health and Safety, CCInfoWeb Databases, 2015
 (Chempendium, RTECs, HSDB, INCHEM).
 European Chemicals Agency, Classification Legislation, 2015
 Material Safety Data Sheet from manufacturer
 OECD- The Global Portal to Information on Chemical Substances - eChemPortal,
 2015

Preparation Date (mm/dd/yyyy) : 06/15/2012

Reviewed Date SDS (dd/mm/yyyy) : 13/04/2015



Revision No. : 2

Revision Information : All (format change)

Other special considerations for handling : Provide adequate information, instruction and training for operators.

HMIS Rating : * - Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe
Health: 3 Flammability: 0 Reactivity: 0

NFPA Rating 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe
 : *Health: 3 Flammability: 0 Instability: 0 Special Hazards: None.*

<p><u>Prepared for:</u> Parker Hannifin Corporation - Sporlan Division 206 Lange Drive, Washington, MO, U.S.A. 63090 Telephone: (636) 239-1111 www.parker.com Direct all enquiries to: Parker Hannifin Corp. - Sporlan Division.</p>	
<p><u>Prepared by:</u> ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.); (888) 977-4834 (Canada) http://www.thecompliancecenter.com</p>	

DISCLAIMER

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by / obtained from Parker Hannifin Corp and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Parker Hannifin Corp expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Parker Hannifin Corp.

END OF DOCUMENT