

Premium Elastic Sealant Cords

SDS Revision Date (mm/dd/yyyy): 04/08/2015

PP33; PP36 Page 1 of 10

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

Premium Elastic Sealant Cords

: PP33 (P/N 475298); PP36 (P/N 475300 Product Code(s)

Recommended use of the chemical and restrictions on use

: Air conditioning and refrigeration sealer slugs for sealing around components.

Chemical family Mixture. This article is an off-white, gray, non-hardening sealing compound. It is

supplied as a bead or tape on a release paper/film.

Name, address, and telephone number

Name, address, and telephone number of

of the supplier:

the manufacturer:

Parker Hannifin Corporation - Sporlan Division

Refer to supplier

206 Lange Drive Washington, MO, U.S.A.

63090

Supplier's Telephone #

: (636) 239-1111

24 Hr. Emergency Tel #

Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887

(Outside U.S.).

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

WHMIS information: This product is not a WHMIS controlled product in Canada. This product is considered to be a 'manufactured article'. The Controlled Products Regulations (CPR) do not apply to manufactured articles [Hazardous Products Act Section 12(i)].

OSHA: This product is considered an 'article' under 29 CFR Part 1910.1200. This material is not classified as hazardous under OSHA regulations (29 CFR Part 1910.1200).

Label elements

The following label information is applicable only to the United States according to OSHA Regulations (29 CFR 1910.1200) (Hazcom 2012):

Signal Word

Not required

Hazard statement(s)

Not required

Precautionary statement(s)

Not required

The following label information is applicable only to Canada according to the Canadian Controlled Products Regulations (CPR/WHMIS):

This product is not a WHMIS controlled product in Canada. As such, this product does not require a WHMIS Supplier label.



Premium Elastic Sealant Cords

SDS Revision Date (mm/dd/yyyy): 04/08/2015

PP33; PP36 Page 2 of 10

SAFETY DATA SHEET

Other hazards

Other hazards which do not result in classification: Burning produces obnoxious and toxic fumes.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS#	Concentration
Calcium carbonate	1317-65-3	60.0 - 80.0
Talc	14807-96-6	0.0 - 0.0

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

Ingestion : Rinse mouth. Do NOT induce vomiting. Never give anything by mouth if victim is

unconscious. If symptoms develop, seek medical attention.

Inhalation : Move to fresh air. If breathing is difficult, give oxygen by qualified medical personnel

only. If breathing has stopped, give artificial respiration. Obtain medical advice.

Skin contact : Remove contaminated clothing. Wash affected areas with soap and water. Wash

contaminated clothing before re-use. If irritation or symptoms develop, seek medical

attention.

Eye contact : Rinse with plenty of water. Lift upper and lower lids during flushing to ensure complete

removal of chemical. If irritation persists, seek prompt medical attention.

Most important symptoms and effects, both acute and delayed

: May cause mild respiratory irritation at higher temperatures. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Indication of any immediate medical attention and special treatment needed

: Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

: Use media suitable to the surrounding fire such as water fog or fine spray, alcohol foams, carbon dioxide and dry chemical.

Unsuitable extinguishing media

: Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

: Not flammable. Burning produces obnoxious and toxic fumes.

Flammability classification (OSHA 29 CFR 1910.106)

: Not flammable.

Explosion Data: Sensitivity to Mechanical Impact / Static Discharge:

: Not expected to be sensitive to mechanical impact or static discharge.

Hazardous combustion products

: Carbon oxides; formaldehyde; Sodium oxides; Other unidentified organic compounds.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.



Premium Elastic Sealant Cords

PP33; PP36 Page 3 of 10

SDS Revision Date (mm/dd/yyyy): 04/08/2015

SAFETY DATA SHEET

Special fire-fighting procedures

: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. Individuals involved in the cleanup must wear appropriate personal protective equipment. For personal protection see section 8.

Environmental precautions

: Ensure spilled product does not enter drains, sewers, waterways, or confined spaces.

Methods and material for containment and cleaning up

: Remove all sources of ignition. Ventilate area of release. Stop the spill at source if it is safe to do so. Clean up promptly by sweeping or vacuum. Place spilled material into a suitable, labelled container for later disposal (see Section 13). Notify the appropriate authorities as required.

Special spill response procedures

If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).

US CERCLA Reportable quantity (RQ): None reportable.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

: Provide adequate ventilation. Use personal protective equipment as required. Avoid breathing fumes. Avoid contact with skin and eyes. Keep away from extreme heat and flame. Keep away from incompatibles. Keep containers closed when not in use. Wash thoroughly after handling.

Conditions for safe storage

: Store in a cool, dry, well-ventilated area. Store away from incompatible materials.

Protect from damage.

Incompatible materials : Acids; Strong oxidizing agents; Bases; Reducing agents .

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:						
Chemical Name	ACGIH TI	<u>_V</u>	OSHA I	OSHA PEL		
	<u>TWA</u>	STEL	<u>PEL</u>	STEL		
Calcium carbonate	N/Av	N/Av	15 mg/m³ (total dust); 5 mg/m³ (respirable)	N/Av		
Talc	2 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	N/Av	N/Av	N/Av		

Exposure controls

Ventilation and engineering measures

: Provide adequate ventilation. If product is processed in a manner that generates dusts or fumes, provide mechanical ventilation to control airbourne exposure levels.



Premium Elastic Sealant Cords

PP33; PP36 Page 4 of 10

SDS Revision Date (mm/dd/yyyy): 04/08/2015

SAFETY DATA SHEET

Respiratory protection : Not required under normal conditions of handling. If product is processed in a manner

that generates dusts or fumes, conduct air monitoring to assess the need for

respiratory propertion. If respiratory protection is warranted, wear NIOSH-approved respirators. Advice should be sought from respiratory protection specialists.

Skin protection : Not required under normal conditions of handling. For prolonged or repeated contact

use protective gloves. Advice should be sought from glove suppliers.

Eye / face protection : Not required under normal conditions of handling. If product is processed in a manner

that generates dusts or fumes, wear as appropriate: Safety glasses with side-shields;

Goggles.

Other protective equipment : An eyewash station and safety shower should be made available in the immediate

working area. Other equipment may be required depending on workplace standards.

General hygiene considerations

: Avoid breathing fumes. Avoid contact with skin and eyes. Do not eat, drink or smoke when using this product. Upon completion of work, wash hands before eating, drinking,

smoking or use of toilet facilities. Remove soiled clothing and wash it thoroughly

before reuse.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : This article is an off-white, gray, non-hardening sealing compound. It is supplied as a

bead or tape on a release paper/film.

 Odour
 : No odour.

 Odour threshold
 : N/Av

 pH
 : N/Ap

 Melting/Freezing point
 : N/Av

Initial boiling point and boiling range

: N/Av

Flash point : None.

Flashpoint (Method) : N/Ap

Evaporation rate (BuAe = 1) : N/Ap

Flammability (solid, gas) : Not applicable.

Lower flammable limit (% by vol.)

N/Ap

Upper flammable limit (% by vol.)

: N/Ap

Oxidizing properties : None.

Explosive properties: Not explosive

Vapour pressure : N/Ap
Vapour density : N/Ap

Relative density / Specific gravity

: 1.6

Solubility in water : insoluble
Other solubility(ies) : Not available.

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: N/Av

Auto-ignition temperature : N/Av

Decomposition temperature: Not available.

Viscosity : N/Ap

Volatiles (% by weight) : Not available.

Volatile organic Compounds (VOC's)

: None.

Absolute pressure of container

: N/Ap



Premium Elastic Sealant Cords

PP33; PP36 Page 5 of 10

SDS Revision Date (mm/dd/yyyy): 04/08/2015

SAFETY DATA SHEET

Flame projection length : N/Ap

Other physical/chemical comments

: None reported by the manufacturer.

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not normally reactive.

Chemical stability : Stable under the recommended storage and handling conditions prescribed.

Possibility of hazardous reactions

: No dangerous reaction known under conditions of normal use.

Conditions to avoid : Avoid heat and open flame. Avoid contact with incompatible materials. Do not use in

areas without adequate ventilation.

Incompatible materials : Acids; Strong oxidizing agents; Bases; Reducing agents .

Hazardous decomposition products

: None known, refer to hazardous combustion products in Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES

Routes of exposure skin absorption

: NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

: May cause mild respiratory irritation at higher temperatures.

Sign and symptoms ingestion

: None expected, when used as intended. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhea.

Sign and symptoms skin : Direct skin contact may result in little or no irritation.

Sign and symptoms eyes : Causes little or no irritation.

Potential Chronic Health Effects

Mutagenicity

None known or reported by the manufacturer.Not expected to be mutagenic in humans.

Carcinogenicity : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects & Teratogenicity

: Not expected to have other reproductive effects.

Senitization to material : Not expected to be a skin or respiratory sensitizer.

Specific target organ effects : Target Organs: Eyes, skin, respiratory system and digestive system.

The substance or mixture is not classified as specific target organ toxicant, single

exposure.


The substance or mixture is not classified as specific target organ toxicant, repeated

exposure.

Irritancy : Causes little or no irritation.

Medical conditions aggravated by overexposure

: None known or reported by the manufacturer.





Premium Elastic Sealant Cords

PP33; PP36 Page 6 of 10

SDS Revision Date (mm/dd/yyyy): 04/08/2015

SAFETY DATA SHEET

Synergistic materials : Not available.

Toxicological data : See below for individual ingredient acute toxicity data.

	LCso(4hr)	LD50 (Oral, rat) (Rabbit, dermal)			
Chemical name	inh, rat				
Calcium carbonate	>3 mg/L	6450 mg/kg	>2000 mg/kg		
Talc	N/Av	N/Av	N/Av		

Other important toxicological hazards

: None known.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: As supplied, this product does not present a physical, health or environmental hazard.

No data is available on the product itself. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

Ecotoxicity data:

<u>Ingredients</u>	2421	Toxicity to Fish				
	CAS No	LC50 / 96h	NOEC / 21 day	M Factor		
Calcium carbonate	1317-65-3	>57000 mg/L (Gambusia affinis)	n/av	none		
Talc	14807-96-6	96 Hr LC50 Brachydanio rerio: >100 g/L [semi-static]	N/Av	None.		

<u>Ingredients</u>	CAS No	То	xicity to Daphnia	aphnia		
	N	EC50 / 48h	NOEC / 21 day	M Factor		
Calcium carbonate	1317-65-3	n/av	n/av	none		
Talc	14807-96-6	N/Av N/Av I		None.		

<u>Ingredients</u>	CAS No	Toxicity to Algae				
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor		
Calcium carbonate	1317-65-3	n/av	n/av	none		
Talc	14807-96-6	N/Av	N/Av	None.		

Persistence and degradability

: No data is available on the product itself.

Bioaccumulation potential

Mobility in soil

No data is available on the product itself.No data is available on the product itself.

Other Adverse Environmental effects

: No data is available on the product itself.

SECTION 13. DISPOSAL CONSIDERATIONS



Premium Elastic Sealant Cords

PP33; PP36

SDS Revision Date (mm/dd/yyyy): 04/08/2015

Page 7 of 10

SAFETY DATA SHEET

Handling for Disposal

: See Section 7 (Handling and Storage) for further details.

Methods of Disposal

: Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for

specific rules.

RCRA

: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14. TRANSPORTATION INFORMATION **Transport** Regulatory **Packing** hazard Label **UN Number** UN proper shipping name Information Group class(es) Not **TDG** None Not regulated. none regulated TDG None. Additional information Not 49CFR/DOT None Not regulated. none regulated 49CFR/DOT None. Additional information ICAO/IATA None. Not regulated. Not none regulated ICAO/IATA None. Additional information

Special precautions for user

Environmental hazards : See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

:

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

<u>Ingredients</u>	TSCA		CERCLA Reportable	SARA TITLE III: Sec. 302, Extremely	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical		
	CAS # Inventory	Quantity(RQ) (40 CFR 117.302):	Hazardous Substance, 40 CFR 355:	Toxic Chemical	de minimus Concentration		
Calcium carbonate	1317-65-3	Yes	N/Ap	N/Av	No	N/Ap	
Talc	14807-96-6	Yes	N/Ap	N/Av	No	N/Ap	

Premium Elastic Sealant Cords SDS Revision Date (mm/dd/yyyy): 04/08/2015 PP33; PP36 Page 8 of 10

SAFETY DATA SHEET

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

<u>Ingredients</u>	CAS#	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Calcium carbonate	1317-65-3	No	N/Ap	No	Yes	Yes	Yes	Yes	Yes
Talc	14807-96-6	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes

Canadian Information:

Canadian WHMIS Classification: Refer to Section 2 for a WHMIS Classification for this product.

Canadian Environmental Protection Act (CEPA): All components of this product are on the Canadian DSL list.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	CAS#	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
Calcium carbonate	1317-65-3	215-279-6	Present	Present	(1)-122	KE-21996	Present	
Talc	14807-96-6	238-877-9	Present	Present	(1)-468; (1)-468	KE-32773	Present	No information available.

SECTION 16. OTHER INFORMATION



Premium Elastic Sealant Cords

PP33; PP36 Page 9 of 10

SDS Revision Date (mm/dd/yyyy): 04/08/2015

SAFETY DATA SHEET

: ACGIH: American Conference of Governmental Industrial Hygienists Legend

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

of 1980

CFR: Code of Federal Regulations DOT: Department of Transportation DSL: Domestic Substances List EPA: Environmental Protection Agency

HMIS: Hazardous Materials Identification System HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer

Inh: Inhalation

LC: Lethal Concentration

LD: Lethal Dose MA: Massachusetts N/Ap: Not Applicable N/Av: Not Available

NFPA: National Fire Protection Association

NIOSH: National Institute of Occupational Safety and Health

NJ: New Jersey

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PA: Pennsylvania

PEL: Permissible exposure limit

RCRA: Resource Conservation and Recovery Act

RI: Rhode Island

RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values

WHMIS: Workplace Hazardous Materials Identification System

1. ACGIH, Threshold Limit Values and Biological Exposure Indices for References

2. Canadian Centre for Occupational Health and Safety, CCInfoWeb Databases,

2015 (Chempendium, RTECs, HSDB, INCHEM).

3. European Chemicals Bureau, Existing Chemicals Work Area, EINECS Information

System, 2014. 4. Material Safety Data Sheet from manufacturer.

5. OECD - The Global Portal to Information on Chemical Substances - eChemPortal,

2014.

Preparation Date (mm/dd/yyyy)

Revision Information

04/14/2012

Reviewed Date SDS (dd/mm/yyyy)

08/04/2015

Revision No. 2

: All (format change)

Health:

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

*- Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe **HMIS Rating**

Flammability:

NFPA Rating 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

Health: Flammability: 0 Instability: 0 Special Hazards: None.

0

Reactivity:



Premium Elastic Sealant Cords SDS Revision Date (mm/dd/yyyy): 04/08/2015 PP33; PP36

Page 10 of 10

SAFETY DATA SHEET

Prepared for:

Parker Hannifin Corporation Sporlan Division 206 Lange Drive, Washington, MO, U.S.A. 63090

Telephone: (636) 239-1111

www.parker.com

Direct all enquiries to: Parker Hannifin Corp. Sporlan

Division.

Prepared by:

ICC The Compliance Center Inc.

Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada)

http://www.thecompliancecenter.com





DISCLAIMER

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by / obtained from Parker Hannifin Corp and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Parker Hannifin Corp expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Parker Hannifin Corp.

END OF DOCUMENT