



Earn more revenue on the air cleaners you install

Our expanded lineup of replacement filters gives you more options to **sell to homeowners based on their unique needs.**



GENUINE **Aprilaire** **Allergy & Asthma**  STOCK NO. **216**

REMOVES 99% OF ASTHMA TRIGGERS

Fits Aprilaire Purifier Models: 1200 | 1620 | 2200 | 2206 | 3200 | 4200

- + MERV 16 performance
- + Low resistance
- + Removes up to 99% of allergy & asthma triggers
- + Superior system protection
- + Up to 6-month filter life



GENUINE **Aprilaire** **Odor Reduction**  STOCK NO. **213** CBN

REMOVES PET & COOKING ODORS

Fits Aprilaire Purifier Models: 1200 | 1620 | 2200 | 2206 | 3200 | 4200

- + MERV 13 performance plus odor reduction
- + The most activated carbon added to any air filter
- + Reduces noticeable odors caused by pets, cooking and common household VOCs
- + Up to 6-month filter life



GENUINE **Aprilaire** **Healthy Home**  STOCK NO. **213**

REMOVES MOST COMMON ALLERGENS

Fits Aprilaire Purifier Models: 1200 | 1620 | 2200 | 2206 | 3200 | 4200

- + MERV 13 performance
- + Designed for homeowners with low-to-moderate allergy problems
- + Low resistance
- + Up to 1-year filter life

GENUINE **Aprilaire** **Clean Air**  STOCK NO. **210**

VACUUM & DUST LESS OFTEN

Fits Aprilaire Purifier Models: 1200 | 1620 | 2200 | 2206 | 3200 | 4200

- + MERV 11 performance
- + Particulate removal, system protection and static pressure superior to 1" filters
- + Vacuum and dust less often
- + Up to 1-year filter life

Filter options by air cleaner



Filter Series	16x20*	20x25**	20x20*	16x25**	31x28	25x20
CLEAN AIR MERV 11	110	210	310	410	510	910
HEALTHY HOME MERV 13	113	213	313	413	513	913
ODOR REDUCTION MERV 13	-	213CBN	-	413CBN	513CBN	-
ALLERGY & ASTHMA MERV 16	-	216	-	416	516	-

*Compatible with 4898 competitive upgrade rails

**Compatible with Easy Install air purifiers and Aprilaire/Space-Gard upgrade kits

REMOVAL EFFICIENCY (Based on Particle Size)

	0.3–1.0 Microns	1.0–3.0 Microns	3.0–10.0 Microns
MERV 16	95%	98%	99%
MERV 13	63%	88%	93%
MERV 11	37%	67%	92%
MERV 10	22%	56%	92%
EAC (Model 5000)	89%	95%	98%

Test Method - MERV 10-16 -ASHRAE 52.2.2012, EAC - AHRI 680-2009