

Product Family
Traps (Slip x Slip)

Description

These fittings are designed to meet most all residential, industrial and irrigation/agricultural needs. Smooth inner walls allow for low pressure drops and resistance to chemicals and corrosion.

Features

- Schedule 40 traps
- Resists chemicals and corrosion

Specifications

Warranty:
1 year



5-408



5-409



5-410



5-411



5-412



5-414



Simplify The Way You Work

6650 Sugarloaf Parkway, Duluth, GA 30097 Phone: 800-955-2222 Fax: 678-542-3700 www.diversitech.com
© 2016 Diversitech Corporation
All rights reserved.

STOCK NO	Description	Dimensions (in)	Type	Max Pressure	Max Temp	Weight (lbs)
5-408	3/4in. P Trap (Slip x Slip)	Depth = 8.00 in Width = 4.75 in Height = 1.00 in	Schedule 40	289 PSI	140°F	0.242 lbs
5-409	3/4in. Running Trap (Slip x Slip)	Depth = 10.75 in Width = 1.00 in Height = 2.50 in	Schedule 40	289 PSI	140°F	0.242 lbs
5-410	3/4in. Mini P Trap (Slip x Slip)	Depth = 6.25 in Width = 1.000 in Height = 4.00 in	Schedule 40	289 PSI	140°F	0.20 lbs
5-411	1in. P Trap (Slip x Slip)	Depth = 8.25 in Width = 1.25 in Height = 5.0 in	Schedule 40	270 PSI	140°F	0.336 lbs
5-412	1/2in. P Trap (Slip x Slip)	Depth = 8.5 in Width = 4.00 in Height = 0.75 in	Schedule 40	358 PSI	140°F	0.20 lbs
5-414	3/4in. J Trap (Slip x Slip)	Depth = 6.00 in Width = 4.00 in Height = 1.00 in	Schedule 40	289 PSI	140°F	22.6 lbs



Simplify The Way You Work

6650 Sugarloaf Parkway, Duluth, GA 30097 Phone: 800-955-2222 Fax: 678-542-3700 www.diversitech.com

© 2016 Diversitech Corporation

All rights reserved.

Rev. 2/3/17

Page 2 of 2