

# Compare our portable power packs



	Batt Pack Energy	Batt Pack Pro	Batt Pack Jupiter
<b>Power</b>	3,000W	5,000W	7,000W
<b>Surge Power</b>	4,500W (500ms) 6,000W (10ms)	7,000W (500ms) 10,000W (10ms)	12,000W (1sec)
<b>Loaded Motor Capacity</b>	+2HP	+3HP	+5HP
<b>Energy</b>	2.5kWh	5.1kWh	7.2kWh
<b>Chemistry</b>	LiFePO4		
<b>Cycles</b>	+3,500 Cycles		+3,000 Cycles
<b>Voltage</b>	120V AC*		120V AC and 240V AC
<b>Frequency</b>	60 Hz		50 Hz / 60 Hz
<b>Solar Input Power</b>	1,600W	5,500W	800W
<b>VOC Input Voltage</b>	60V DC	320V DC	29-75V DC
<b>Solar Input Voltage</b>	30-60V DC	125-320V DC	60V DC
<b>Max Solar Amperage</b>	40A		30A
<b>Grid Charging Power</b>	1,200W	1,400W	1,110W
<b>Bypass Power</b>	1,200W		N/A
<b>Sine Wave</b>	Pure Sine Wave		
<b>Output Voltage Threshold</b>	5%		
<b>Dimensions</b>	60.5cm x 39.4cm x 33.6cm [23.8in x 15.5in x 13.2in]	65cm x 50.8cm x 30cm [25.6in x 20in x 11.8in]	91.4cm x 68.5cm x 58.4cm [36in x 27in x 23in]
<b>Weight</b>	36 kg [79.4 lbs]	63.5 kg [140 lbs]	127 kg [280 lbs]
<b>Storage Temperature</b>	-30°C to 50°C [-22°F to 122°F]		-20°C to 45°C [-4°F to 113°F]
<b>Operating Temperature</b>	-30°C to 50°C [-22°F to 122°F]		-20°C to 45°C [-4°F to 113°F]
<b>Idle Power Consumption</b>	40W	70W	N/A
<b>Certification</b>	UL9540A, UL1642, CSA SPE-1000, UL1741		CSA SPE-1000, UL-458
<b>Safety Features</b>	• Solar reverse polarity protection	• Short circuit protection • Over temperature shut off	• Overload protection

\* 240V AC 50 Hz model available upon request, subject to MOQs  
 \*\*Custom colours available, subject to MOQs.



**ATTENTION:** Please note it is the customer's obligation to check local electrical requirements and certification requirements of all HPS purchased equipment to ensure they meet the local electrical code. Additional components such as AFCI protection, Conduit Caps, and fusing/breakers may be required.