

16 SEER

CHANGE

9, 12, 18 & 24,000 BTU



**1 in 3 air conditioners sold worldwide is made by GREE.
Professionals you can trust.**

The DC Inverter Change series heat pump uses GREE's advanced G10 technology, which enables the unit to operate in ultra low frequency and to precisely control the indoor temperature. It also offers a reduced energy consumption and lower noise level. Change for a better life.

TECHNICAL SPECIFICATIONS

	AIR CONDITIONERS				HEAT PUMPS			
Nominal cooling (BTU/h)	9,000	12,000	18,000	24,000	9,000	12,000	18,000	24,000
Indoor model	GWC09KFD3DNA5C0	GWC12KFD3DNA5C0	GWC18KGD3DNA5E0	GWC24KGD3DNA5A0	GWH09KFD3DNA5C0	GWH12KFD3DNA5C0	GWH18KGD3DNA5E0	GWH24KGD3DNA5A0
Outdoor model	GWC09KFD3DNA6C1	GWC12KFD3DNA6C1	GWC18KGD3DNA6E1	GWC24KGD3DNA6A1	GWH09KFD3DNA6C1	GWH12KFD3DNA6C1	GWH18KGD3DNA6E1	GWH24KGD3DNA6A1
PERFORMANCE RATINGS/ELECTRICAL DATA								
BTU/h (cooling)	9,000 (3,800-11,500)	12,000 (3,300-12,500)	18,000 (4,500-21,000)	22,000 (6,400-24,000)	9,000 (3,800-11,500)	12,000 (3,300-12,500)	18,000 (4,500-21,000)	22,000 (6,400-24,000)
BTU/h (heating)					9,000 (3,300-11,500)	12,000 (3,400-12,500)	21,000 (4,000-23,000)	26,600 (4,100-26,600)
Voltage/frequency	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
SEER	16	16	16	16	16	16	16	16
HSPF					8.5	8.5	8.5	9.5
EER	10.58	10.34	11.1	10	10.58	10.34	11.1	10
Heating operating range °C (°F)					-15-23 (5-75)	-15-23 (5-75)	-20-23 (-4-75)	-15-23 (5-75)
Cooling operating range °C (°F)	-15-43 (5-109)	-15-43 (5-109)	-15-48 (5-118)	-15-45 (5-114)	-15-43 (5-109)	-15-43 (5-109)	-15-48 (5-118)	-15-45 (5-114)
Moisture removal Pt./h(l/h)	0.38	0.66	3.8	5	0.38	0.66	3.8	5
Indoor air circulation C.F.M. (hi/medium/low)	330/300/260	340/300/260	471/400/330	1000/800/700	(330/300/260)	(340/300/260)	471/400/330	589/441/306
Indoor noise level (dB-A) (hi/medium/low/quiet)	43/38/32/26	43/38/32/26	48/43/38/34	49/43/39/34	43/38/32/26	44/39/33/28	48/43/38/34	49/43/39/34
Outdoor noise level (dB-A)	49	52	56	53	49	52	56	53
REFRIGERATION SYSTEM								
Liquid line O.D. (in)	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4
Suction line O.D. (in)	3/8	3/8	1/2	1/2	3/8	3/8	1/2	1/2
Max. line length (ft)	49.2	49.2	82	82	49	49.2	82	82
Max. height difference (ft)	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8
INDOOR UNIT DIMENSIONS (in)								
Height	11 5/32	11 5/32	12 1/32	12 9/16	11 5/32	11 5/32	12 1/32	12 9/16
Width	30 5/16	30 5/16	34 1/16	39 11/16	30 5/16	30 5/16	34 1/16	39 11/16
Depth	7 29/32	7 29/32	8 15/32	8 11/16	7 29/32	7 29/32	8 15/32	8 11/16
OUTDOOR UNIT DIMENSIONS (in)								
Height	21 3/4	21 3/4	27 5/8	27 5/8	21 3/4	21 3/4	27 5/8	27 5/8
Width	28	28	37 29/32	37 29/32	28	28	37 29/32	37 29/32
Depth	12 1/2	12 1/2	15 5/8	15 5/8	12 1/2	12 1/2	15 5/8	15 5/8



GREE products are subject to continuous improvements. GREE reserves the right to modify product design, specifications and information without notice and without incurring obligations.



Authorized dealer



CHANGEENGES0414

