







ELECTRONIC WINDOW AIR CONDITIONER

The Curve line of window air conditioners is an economical cool-

ing option for the summer, ranging from 350 to 700 square feet,

depending on the model, and features electronic controls and a multi-function remote. In addition to cooling your room, these

units reduce humidity and mold to improve air quality.































3-IN-1 UNIT



















IFEEL TECHNOLOGY

Nothing is worse than an inaccurate thermostat. When you use the iFeel feature, the air conditioner uses a sensor on the remote control that feels the room temperature at its location and communicates with the unit to adjust the temperature and airflow efficiently and accurately.

INSTALLATION KIT

The extendable side panels and all hardware required for horizontal installation in a double-hung window are included with the purchase of this air conditioner. Installation is a snap by following the simple instructions in the user's manual, also included.

REUSABLE FILTER

Keep dust out of the air and your unit running smoothly with our easy-to-clean filter. The cleaning reminder will alert you after 250 hours of operation that a filter cleaning is due to ensure the efficiency of your air conditioner.



		MODEL	CURVE 8	CURVE 10	CURVE 12	CURVE 15
Product Code:		GJC08BK-A6NRNE***	GJC10BL-A6NRNE**	GJC12BR-A6NRNE**	GJC15BY-A6NRNE**	
Power Supply		V/Hz/Ph	115 / 60 / 1	115 / 60 / 1	115 / 60 / 1	115 / 60 / 1
Capacity	Cooling	BTU/hr	8000	10200	12100	15000
Coverage		m² (sq ft)	32.5 (350)	41.8 (450)	51.1 (550)	65.0 (700)
EER		BTU/W*hr	12.1	12.1	12.1	11.9
Energy Star®		_	YES	YES	YES	YES
Rated Output		W	850	1030	1150	1490
Rated Current A		A	6.6	8.9	10.3	14.5
Moisture Removal L/d		L/d (pt/d)*	28.1 (59.3)	34.6 (73.0)	42.2 (89.3)	44.4 (93.8)
Airflow Volume m ³		m³/hr (CFM)	320 / 340 / 360 (188 / 200 / 212)	390 / 420 / 450 (230 / 247 / 265)	400 / 450 / 500 (294 / 265 / 235)	600 / 660 / 700 (353 / 388 / 412)
Sound Level dB		dB	53 / 56 / 59	55 / 57 / 59	55 / 57 / 59	56 / 58 / 60
Adjustable Temperature Range °C (°F		°C (°F)	16 to 30 (61 to 86)	16 to 30 (61 to 86)	16 to 30 (61 to 86)	16 to 30 (61 to 86)
Dimensions	LxHxP	mm (in)	472 x 324 s 400 (18.6 x 12.8 x 15.7)	483 x 370 x 540 (19 x 14.6 x 21.3)	542 x 400 x 545 (21.3 x 15.7 x 21.5)	600 x 450 x 660 (23.6 x 17.7 x 26)
Weight	Net	kg (lb)	23 (50.7)	28.5 (62.8)	33.0 (72.8)	47 (103.6)
	Gross	kg (lb)	26 (57.3)	32.0 (70.5)	37.0 (81.6)	52.5 (115.7)

^{*} US pint: 0.473L



