

CAMERA

TD-9525A1

2MP Face Detection Dome AI
Network Camera



- Max. resolution: 1920 × 1080
- H.265+/H.265/H264+/H264/MJPEG coding
- 20 ~ 30m white light view distance; Motorized lens
- 3D DNR, digital WDR, BLC, HLC, Defog, ROI coding
- One CVBS output and one one-board CVBS output
- One MIC IN; One built-in MIC; Hardware Reset
- Built-in micro SD card slot, up to 128GB
- DC12V/PoE power supply
- Support smart phone, iPad, remote monitoring
- P2P function optional
- IP67 ingress protection; Support three streams
- Support face detection
- Intelligent Analytics (optional): object removal detection, abnormal video signal detection, line crossing detection, region intrusion detection, people intrusion detection, people counting detection and crowd density detection



en.tvt.net.cn

For more information, please visit our website

Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 23rd Floor, Block B4, Building NO.9, Shenzhen Bay
Eco-Technology Park, Nanshan District, Shenzhen, Guangdong
Province, P.R.China

Tel: +86-755-36995888

Web site: <http://en.tvt.net.cn>

Fax: +86-755-33104777

E-mail: overseas@tvt.net.cn


SPECIFICATIONS

| Model | TD-9525A1 |
|--------------------------------|--|
| Specifications | |
| Camera | |
| Image Sensor | 1 / 2.8 "CMOS |
| Image Size | 1920 × 1080 |
| Electronic Shutter | 1 / 25 s ~ 1 / 100000 s |
| Iris Type | Fixed Iris |
| Min. Illumination | 0 lux |
| Lens | 2.8~12mm@F1.4; Horizontal field of view: 93.2°~38.7° Recommended face capturing distance: 1.5~7m |
| Lens Mount | Φ14 |
| Wide Dynamic Range | Digital WDR |
| BLC | Yes |
| HLC | Yes |
| Defogging | Yes |
| Digital NR | 3D DNR |
| Angle Adjustment | Pan: 0°~360°; Tilt: 0°~80°; Rotation: 0°~360° |
| Image | |
| Video Compression | H.265+ / H.265 / H.264+ / H.264 / MJPEG |
| H.264 Compression Standard | Baseline Profile/Main Profile/High Profile |
| Resolution | 1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 × 240 |
| Main Stream | 60Hz : 1080P/ 720P (1 ~ 30fps); 50Hz : 1080P/ 720P (1 ~ 25fps) |
| Sub Stream | 60Hz : D1/CIF (1~30fps); 50Hz:D1/CIF (1~25fps) |
| Third Stream | 60Hz : CIF/480x240 (1~30fps); 50Hz: CIF/480x240 (1~25fps) |
| Bit Rate | 128 Kbps ~ 6 Mbps |
| Bit Rate Type | VBR / CBR |
| Image Settings | ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. adjustable through client software or web browser |
| ROI | Each ROI to be configured separately |
| Interfaces | |
| Network | RJ45 |
| Video Output | CVBS video output (BNC × 1); On-board CVBS output × 1 |
| Audio | MIC IN × 1; Built-in MIC × 1 |
| Storage | Built-in micro SD card slot, up to 128GB |
| Hardware Reset | Yes |
| Functions | |
| Remote Monitoring | Web browsing, CMS remote control |
| Online Connection | Support simultaneous monitoring for up to 6 users; Support multi-stream real time transmission |
| Network Protocol | Ipv4, Ipv6, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP, HTTPs, QoS |
| Interface Protocol | ONVIF |
| Storage | Network remote storage; micro SD card storage |
| Smart Alarm | Motion detection; SD card error; SD card full |
| Intelligent Analytics | Object removal detection, regional intrusion detection, abnormal video detection, line crossing detection, people intrusion, people counting, crowd density, face detection (optional) |
| General function | Watermark, IP address filtering, video mask, heartbeat, password protection |
| PoE | Yes (802.3af) |
| LED View Distance | 20 ~ 30 m |
| Ingress Protection | IP67 |
| Face Detection | |
| Face Detection | Pupil distance of a facial image over 20 pixel can be detected |
| Face Capturing | By precision detecting, tracing, capturing, scoring and screening the moving faces to get the most effective face snapshots |
| Panorama Capturing | Support panorama capturing and self-defined information overlay, like device ID, time, etc. |
| Intelligent Light Compensation | Built-in high efficient white light LEDs, time switch available |

Others

| | |
|-----------------------|--|
| Power Supply | DC12V/PoE |
| Power Consumption | < 12.5W |
| Operating Environment | - 30 °C ~ 60 °C (-22°F~140°F) Humidity: less than 95 % (non-condensing) |
| Dimensions (mm) | Φ 111.5 × 99.6 |
| Weight (net) | Approx. 0.67KG |
| Installation | Wall mounting; ceiling mounting |

DIMENSIONS



AVAILABLE ACCESSORIES



AVAILABLE MODEL

| | |
|-----------------|------------------------|
| Available Model | TD-9525A1(D/AZ/PE/AR2) |
|-----------------|------------------------|