

Scheda tecnica calzatura/Shoes technical data sheet


Identificazione articolo/Item identification					
Cod. comm.le Industrial Starter/ IS commercial item code:	44400	Cod. art. fornitore/ Supplier item code*:	IS03 petroleum	Cod. fornitore/ Supplier code:	101479
Cod. colore Industrial Starter/ Industrial Starter colour code:	-	[X]	Articolo del catalogo/Item from catalogue		
		[-]	Articolo personalizzato/Customized item		
		Codice cliente/Customer code:		N/A	
Nome articolo/Item name:	"SLIP ON – STRETCH EXTREME S1P SRC"				

Descrizione tecnica dell'articolo/Technical item description			
Componente / Component	Materiale / material	Composizione / Composition	Spessore / Thickness
Puntale / Toe	Microfibra / Microfiber	50% nylon + 50% poliuretano / 50% nylon + 50% polyurethane	0.8 mm
Laterale / Vamp	Sandwich mesh / Sandwich mesh	100% terylene / 100% terylene	
Occhiello / Eyestay	Stampa / Printing		
Gambetto / Back Quarter	Microfibra / Microfiber	50% nylon + 50% poliuretano / 50% nylon + 50% polyurethane	1.4 mm
Collarino esterno + linguetta / Outside collar + tongue	Lycra + 1.5 mm SBR / Lycra + 1.5mm SBR	85% nylon + 50% poliuretano	
Tallone / Heel	Microfibra / Microfiber	50% nylon + 50% poliuretano / 50% nylon + 50% polyurethane	1.4 mm
Gancio / Hook	Plastica / Plastic	Nylon / Nylon	
Fettuccia / Webbing	Tessuto / Webbing	Poliestere / Polyester	
Fodera / Lining	Mesh / Mesh	Terylene + PPG + tricot / Terylene + PPG + tricot	
Lacci / Laces	Poliestere / Polyester		
Fodera anteriore / Front Lining	Sandwich mesh / Sandwich mesh	100% terylene / 100% terylene	
Imbottitura collare / Collar padding	Schiuma / Foam	PPG / PPG	10 mm
Sottopiede copertura / Footbed cover	Mesh / Mesh	100% terylene / 100% terylene	
Sottopiede fondo posteriore / Footbed bottom back	Polietilene Alta Densità / Hi Poly	PPG / PPG	
Sottopiede fondo anteriore/ Footbed bottom front	Polietilene Alta Densità / Hi Poly	PPG / PPG	
Lamina antiperforazione / Lasting Board	4 mm Lasted Board / 4 mm Lasted Board	Terilene + Gomma / Terylene + Rubber	4 mm

Scheda tecnica calzatura/Shoes technical data sheet



Puntale / Toe Cap	Composito / Composite	Fibra di vetro + nylon / Fiber Glass + nylon
Suola / Outsole	Poliuretano / Polyurethane	Poliuretano / Polyurethane
Intersuola / Midsole	Poliuretano / Polyurethane	Poliuretano / Polyurethane
Cambrione / Shank	Plastica / Plastic	Nylon / Nylon
Loghi / Logos :		
Taglie / Sizes:	36-48	
Imballo / Packaging:	n. 1 prs / box – n. 5 boxes / export carton	
Note / Notes:	Shank System <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  TEXTILE </div> <div style="text-align: center;">  FIBER GLASS </div> <div style="text-align: center;">  METAL FREE </div> <div style="text-align: center;">  ULTRA FLEX </div> </div>	

Conformità alle norme CE/Conformity with EC standards

Cat.DPI / PPE Category:	II	Norme CE e livelli di protezione/ EC standards and protection levels:	EN ISO 20345: 2011 S1P SRC	
Certificato d'esame UE del tipo n° / UE type-examination certificate No.:		BP 50528866 0001	Data / Date:	14.01.2022
Organismo notificato/ Notified body:		TuV Rheinland	N°/ No.:	0197
Lingue nota informativa/ Information note's languages:		FR / RS / SK / HR / SI / IT / EN / ES / CZ / PL / PT		



Foto / Photo



Vicenza (Italy), 10/02/2022

Resp. acquisti/Purchasing manager