

QUICK SIGHT CAMERAS



OS20

Recommended Pipe Diameter: 1.25"- 2"

- 20m/60ft fiberglass push rod (red)
- 14mm camera head
- 7" monitor
- 14mm camera head
- Glass lens cover, 6 LEDs
- 4.8mm push cable
- On-Screen distance counter
- 1x Rechargeable battery lasts up to 8 hours and charging cable
- 1x Car battery charger
- Rotatable cable reel mounts in case for
- convenient operation
- Waterproof ABS case



QS30

Recommended Pipe Diameter: 2"- 4"

- 30m/100ft fiberglass push rod (blue)
- Push cable dia. 5.2mm
- 23mm camera head
- Built-in 512hz sonde
- 7" I C.D. color monitor
- SD Card and reader included
- On-Screen distance counter
- Waterproof ABS suitcase with all parts included
- Rechargeable battery lasts up to 8 hours
- I x power adapter
- I x car charger
- Two plastic guides for camera head, 46mm & 80mm
- Weight: 21.75 lbs



QS40

Recommended Pipe Diameter: 2"- 4"

- 40m/130ft fiberglass push rod (blue) Two plastic guides for camera head, 46mm & 80mm
- Push cable dia. 5.2mm
- 23mm camera head
- Built-in 512hz sonde
- Smart Breaking System
- 7" monitor with DVR feature
- Stainless steel camera head. IP68 waterproof level
- SD Card and reader included
- Rechargeable battery lasts up to 6 hours
- On-Screen distance counter
- Wireless Keyboard for text input (English)
- Whole system waterproof (box closed)
- I x power adapter
- I x car charger
- Weight: 22.5 lbs



- SELF LEVELING
- Built-in 512hz sonde
- Smart Breaking System
- 7" monitor with DVR feature
- Stainless steel camera head, IP68 waterproof level
- 40m/130ft fiberglass push rod (blue) Two plastic guides for camera head, 46mm & 80mm
 - SD Card and reader included
 - Rechargeable battery lasts up to 6 hours
 - On-Screen distance counter
 - Wireless Keyboard for text input (English)
 - Whole system waterproof (box closed)
 - I x power adapter

Recommended Pipe Diameter: 2"- 4"

- I x car charger
- Weight: 22.5 lbs

WWW.DRAINGEAR.COM

- QS40SL



QS40R **Recommended Pipe Diameter: 3"- 6"**

- Push cable dia. 6.8mm
- 23mm camera head
- Built-in 512hz sonde
- Smart Breaking System
- 7" monitor with DVR feature
- Stainless steel camera head,
- IP68 waterproof level
- 30m/100ft fiberglass push rod (RED) Two plastic guides for camera head, 46mm & 80mm
 - SD Card and reader included
 - Rechargeable battery lasts up to 6 hours
 - On-Screen distance counter
 - Wireless Keyboard for text input (English)
 - Whole system waterproof (box closed)
 - I x power adapter
 - I x car charger
 - Weight: 22.5 lbs



QS40RSL **Recommended Pipe Diameter: 3"- 6"**

- Push cable dia. 6.8mm
- 23mm camera head
- Built-in 512hz sonde - SELF LEVELING
- Smart Breaking System
- 7" monitor with DVR feature
- Stainless steel camera head. IP68 waterproof level
- 30m/100ft fiberglass push rod (RED) Two plastic guides for camera head, 46mm & 80mm
 - SD Card and reader included
 - Rechargeable battery lasts up to 6 hours
 - On-Screen distance counter
 - Wireless Keyboard for text input (English)
 - Whole system waterproof (box closed)
 - I x power adapter
 - I x car charger
 - Weight: 22.5 lbs


Spare Parts



23mm Camera Head with 512Hz Sonde

23mm Camera Head with 512 Hz Sonde & SL





6.8mm Push Rod (Red) 30m



Display Pannel	
QS20/30	

Display Pannel QS 40 / 40R / 40SL / 40RSL

