

Nano POS



VESA Mount Capable*

* VESA pole & bracket are not included.



Aluminium Die-cast Casing



Removable HDD/SSD

SE/MOR



| SPECIFICATIONS | Nano POS 6200 | Nano POS 6320 | Nano POS 6520 |
|----------------|-----------------------------|------------------------------|------------------------------|
| PROCESSOR | Intel Celeron J1900 2.0 GHz | Intel Core i3-4330TE 2.4 GHz | Intel Core i5-4570TE 2.7 GHz |
| SYSTEM MEMORY | 4 GB DDR3L RAM (up to 8 GB) | 4 GB DDR3 RAM (up to 8 GB) | |
| STORAGE | 2.5" removable SATA HDD/SSD | | |

DISPLAY

| | |
|--------------------|---------------------------------------|
| SIZE / RESOLUTION | 15" TFT LCD / 1024 x 768 pixels |
| BRIGHTNESS | 350 cd/m ² |
| TOUCH SCREEN PANEL | Projected capacitive touch (10-point) |

I/O INTERFACE

| | | |
|------------------|---------------------------|---------------------------|
| USB PORT | 3 x USB 2.0, 1 x USB 3.0 | 2 x USB 2.0, 2 x USB 3.0 |
| SERIAL PORT | 3 x DB9, 1 x RJ50 | 2 x DB9, 1 x RJ50 |
| VIDEO PORT | 1 x VGA | 1 x VGA |
| AUDIO PORT | 1 x mic-in, 1 x line-out | 1 x mic-in, 1 x line-out |
| CASH DRAWER PORT | 1 x RJ12 (12 V) | 1 x RJ12 (12 V) |
| ETHERNET PORT | 1 x RJ45 10/100/1000 Mbps | 1 x RJ45 10/100/1000 Mbps |

OPERATING SYSTEM

| | |
|---------|--------------------------------------|
| WINDOWS | POSReady 7 / 7 Pro / 10 IoT / 10 Pro |
|---------|--------------------------------------|

ENVIRONMENT & MECHANICAL SPECIFICATIONS

| | | |
|---------------------|--|--|
| DIMENSIONS & WEIGHT | 324 (W) x 264 (H) x 368 (D) mm 7.8 kg | |
| CHASSIS MATERIAL | Heat-dissipating solid aluminium die-cast casing | |
| TEMPERATURE | Operating: 0°C to 35°C Storage: -20°C to 60°C | |
| HUMIDITY | Operating: 20% to 80% (non-condensing) | |
| POWER CONSUMPTION | 19 V / 4.74 A, external power adaptor, 100-240 V, 50/60 Hz | 19 V / 7.89 A, external power adaptor, 100-240 V, 50/60 Hz |

MODEL OPTIONS

| | |
|-------------------------|---|
| INTEGRATED CARD READERS | 3-track MSR / Fingerprint reader / RFID reader (13.56 MHz, 125 kHz) |
| CUSTOMER DISPLAY | 10"/15" TFT LCD display (1024 x 768 pixels) or 2-line VFD |
| SCANNER | 1D / 2D scanner |
| MOUNTING TYPE | Desktop / VESA mount |

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
F: +61 7 3275 5800
sales@senortech.com.au

SENIOR
TOUCH SCREEN SOLUTIONS

Quality. Safety. Versatility.