

# POS PERIPHERALS

Customer Display | Scanner | UPS | Printer | Cash Drawer

## CUSTOMER DISPLAY

### 10" or 15" LCD



Available in  
10" & 15" LCD Display

### 8.4" LCD



Available in  
8.4" LCD Display

### VFD CUSTOMER POLE DISPLAY

- 2 Lines x 20 Characters Vacuum Fluorescent Pole Display
- 40 Characters
- Character Size 5.25 x 9.5 mm
- Display Colour Green or Blue
- ESC/POS (Epson) Emulation
- Long & Short Pole (included)
- Serial/USB Interface
- External Power Supply 12V (included)
- Dimensions:
  - Long 225(W) x 10(D) x 560(H) mm
  - Medium 225(W) x 10(D) x 285(H) mm
  - Short 225(W) x 10(D) x 195(H) mm



## BARCODE SCANNER

### GSN-320 Handheld CCD Scanner

- Handheld Contact CCD Scanner
- 2,500 pixels CCD
- Scan Rate 150 scans per second
- Designed to withstand 1.5m drops



### ST-351HS Handheld Laser Scanner with Cradle

- Handheld High-Speed Laser Scanner
- Single Line Laser
- Auto Scan in Stand Mode
- Scan Rate 500 scans per second
- Designed to withstand 1m drops
- Available interface: Keyboard/RS232/HID USB/USB Virtual COM/OPOS/JPOS



### GSN-391BT Handheld Bluetooth Scanner with Cradle

- Wireless Handheld Laser Scanner
- Single Line Laser
- Scan Rate 100 scans per second
- Designed to withstand 1m drops
- Up to 100m Wireless Range
- Available Interface: Keyboard/RS232/HID USB/USB Virtual COM/wand/OPOS/JPOS



### GSN-697 Hands Free Orbit Laser Scanner

- Orbit Dual-Laser Omni-directional Scanner
- 650 nm visible laser diode (VLD)
- 5 directions of scan field
- 20 Lines Lasers
- Scan Rate 1,400 scans per second
- Designed to withstand 1m drops
- Available interface: Keyboard/RS232/HID USB/USB Virtual COM/OPOS/JPOS



### GSN-6112 Hands Free 2D Image Laser Scanner

- Compact Hands Free 2D Image Laser Scanner
- 650 nm visible laser diode (VLD)
- Designed to withstand 1.5m drops
- 2D Barcode Decoding Capability: PDF 417, MicroPDF 417, Maxicode, DataMatrix Inverse, QR Code, QR Inverse, MicroQR Code, Aztec Code, Aztec Inverse, Postal Code



## BATTERY BACKUP

### Micro UPS 700 VA (up to 30mins)

- 3 battery backup outlets with surge protection
- Automatic Voltage Regulation (AVR) for clean, stable power; 2 boost and 1 back
- Super smart charger for fast charging time
- Multiple LEDs indicate UPS statuses
- DC cold start (turn on without AC power input)
- Off-mode battery charging



# SE NOR

# POS PERIPHERALS

## THERMAL RECEIPT PRINTER

### TP-250III



- Direct Thermal
- Fast Printing Speed 250mm/sec
- Auto-Cutter with Tear Bar
- High Speed USB 2.0 standard onboard (480Mbps)
- Two Colour Printing (on specially coated Paper)
- 2D Barcode printing support: PDF417, QR-Code
- Internal Buzzer & Water resistant
- Multi-Language text, logo & Graphics Printing
- Wall Mount Option Available
- Paper Roll Size: 79.5 +/- 0.5(W) x 83(Max)mm
- Dimensions: 145(W) x 195(D) x 146(H)mm
- Available interface: RS232 Serial+USB/LPT Parallel+USB/Ethernet+USB/USB only

### TP-100USE/ TP-100USW



- Direct Thermal
- Fast Printing Speed 250mm/sec
- Auto-Cutter with Tear Bar
- High Speed USB 2.0 standard onboard (480Mbps)
- 2D Barcode printing support: PDF417, QR-Code
- Internal Buzzer & Water resistant
- Multi-Language text, logo & Graphics Printing
- Wall Mount Option Available
- Paper Roll Size: 79.5 +/- 0.5(W) x 83(Max)mm
- Dimensions: 145(W) x 195(D) x 148(H)mm
- Available interface: RS232 Serial+USB+Ethernet/RS232 Serial+USB+Wifi

## DOT MATRIX PRINTER

### DP-220

- Serial Impact Method
- Auto Paper Cutter
- Built-in Power Supply
- Print alarm buzzer for noisy places
- Multi-Language text
- Logo and Graphic Printing
- Wall Mount Option Available



- Paper Roll Width 76+/-0.5, 69.5+/-0.5, 57.5+/-0.5mm
- Fast Printing Speed 5.1 LPS (Lines Per Second)
- Auto-Cutter with Tear Bar
- Dimensions: 160(W) x 239(D) x 157(H)mm
- Available interface: RS232 Serial/LPT Parallel/Ethernet/USB

## CASH DRAWER Heavy duty, rugged, steel construction for demanding environments

### KC-4141/ KC-4646



Standard/Classic


#### KC-4141

- 2 Media Slots
- Connector cable 1.50 metres from the top of drawer
- Dimensions: 410(W) x 410(D) x 100(H)mm
- Available interface: RJ12
- 5 Bills/8 Coins, Removable with Wire Gripper, Stainless steel front panel
- 12V or 24V, 1A(24 ohm) with Micro-Switch
- 3 way Key Lock

### KC-4617/ KC-3540

#### KC-4617

- 7 Bills/5 Coins
- Connector cable 1.50 metres from the bottom of drawer
- Dimensions: 460(W) x 170(D) x 100(H)mm
- 1 Media Slot
- 12V or 24V, 1A(24 ohm) with Micro-Switch
- Available interface: RJ12



Flip Top

#### KC-3540

- 4 Bills/8 Coins, Removable with stainless steel top panel
- Connector cable 1.50 metres from the bottom of drawer
- Dimensions: 350(W) x 40(D) x 90(H)mm
- 1 Media Slot
- 12V or 24V, 1A(24 ohm) with Micro-Switch
- Available interface: RJ12



Compact



Heavy Duty

#### KC-4646

- 2 Media Slots
- Connector cable 1.50 metres from the top of drawer
- Dimensions: 460(W) x 460(D) x 100(H)mm
- Available interface: RJ12
- 5 Bills/8 Coins, Removable with Wire Gripper, Stainless steel front panel
- 12V or 24V, 1A(24 ohm) with Micro-Switch
- 3 way Key Lock

### The Senor Building

65 & 67 Weaver Street  
Coopers Plains QLD 4108  
Brisbane, Australia  
[www.senortech.com.au](http://www.senortech.com.au)

P: +61 7 3275 5888  
F: +61 7 3275 5800  
[sales@senortech.com.au](mailto:sales@senortech.com.au)

**SENIOR**  
TOUCH SCREEN SOLUTIONS