



# SlowStop® IronFlex 4" Horseshoe Bollard (SS4Y-28-HS-36)


Color: RAL 1023 Safety Yellow Bollard  
RAL 9005 Black Base

Diameter: 4" (3.5" ANSI Schedule 40 or Equiv.)  
Height: 28"  
Width: 36"

Set Screws: M16 x 2.00mm Hex



Installs with eight (8)  
5/8" x 5-1/2"  
Concrete Anchor Screws



MASS (LBS)	1000	2000	3000	4000	5000	10000	15000	20000	25000	30000	40000	
SPEED (MPH)												
1.0	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	
1.5	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	
2.0	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	
2.5	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	
3.0	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	
4.0	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	
5.0	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	
6.0	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	
7.0	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	
8.0	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	
9.0	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	
10.0	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	
11.0	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	
12.0	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	



**SPECIFICATIONS**

- Stopping Power Rating: 10,668 joules /7,868 ft-lb.
- Temperature Rating: -40°
- Pipe Coating: 60µm Hot Dipped Galvanized + 60µm Polyester Outdoor Powder Coat
- Cast Iron Coating: Environmentally Friendly Water-Based E-Coat + Powder Coat C5I Rated
- Meets IBC 1607.8.3 requirements to resist 6,000 pounds of force at 27" height

**RECOMMENDED USES**

- Fuel Pump Protection
- Equipment and Storage Rack Guarding
- Drive-Thru Lanes
- Utility Protection
- Column Protection
- Access Denial
- Min. 6" 3000 PSI Concrete
- Not for K-Rated Security Use



4955 Stout Dr. • San Antonio, TX 78219  
210-736-4477 • 800-736-5256 • Fax 210-734-6448  
Email: [info@slowstop.com](mailto:info@slowstop.com)  
[www.slowstop.com](http://www.slowstop.com)



QR: Download Spec Sheets  
©2021 SlowStop. All rights reserved.