



Automatic Butterfly Valve with 1/2 Moon Stops

Our Automatic Butterfly Valves are pneumatically operated and electrically controlled. The pneumatic cylinder requires 90 psi to operate but uses very little volume. A single-acting solenoid activates the cylinder. The solenoid is activated by virtually any electrical signal 12/24 V, AC/DC, or 110/220 line voltage. These solenoids operate off of milliamps and therefore require minimal wiring.



AUTO BUTTERFLY			
Ø	Blade Gauge	Cylinder Size and Stroke	Shaft Size
3"	14	1.06 x 3"	1/2
4"	14	1.06 x 3"	1/2
5"	14	1.06 x 3"	1/2
6"	14	1.06 x 3"	1/2
7"	14	1.06 x 6"	1/2
8"	14	1.06 x 6"	1/2
9"	14	1.06 x 6"	1/2
10"	14	1.06 x 6"	1/2
11"	14	1.06 x 6"	1/2
12"	14	1.06 x 6"	1/2
13"	14	1.06 x 6"	1/2
14"	14	1.06 x 6"	1/2
15"	14	1.06 x 6"	1/2
16"	14	1.06 x 6"	1/2
17"	14	1.06 x 6"	1/2
18"	14	2.5 x 6"	1"
19"	14	2.5 x 6"	1"
20"	14	2.5 x 6"	1"
22"	14	2.5 x 6"	1"
24"	14	2.5 x 6"	1"

