



Spark Trap

Reduces sparks from metal grinding, welding and cutting applications. Our spark trap is designed for no minimum distance requirements so it can be placed adjacent to the collector.

- Reduce explosion risks
- AKA: Spark Arrestor or Spark Eliminator
- Works in a vertical or horizontal position
- Products come with raw ends. Diameters are +/- 1/8 inch.



Spark Trap						
Inlet	Outside Dia of Mid Section (D2)	Overall Length (L)	Dropout: (A)	Dropout: (B)	Dropout: (C)	Clean-Out Door (CO)
4	8	36	4	8	4	6x8
5	9	40	5	8	4	6x8
6	11	45	6	8	4	8x10
7	12	41	7	8	4	8x10
8	14	46	8	8	4	8x10
9	16	48	9	8	4	8x10
10	18	51	10	8	4	8x10
12	22	59	12	8	4	10x12
14	25	66	14	14	6	10x12
16	29	70	16	14	6	10x12
18	33	78	18	14	6	12x14
20	36	81	20	14	6	12x14
22	40	85	22	14	6	12x14
24	44	96	24	14	6	12x14
26	46	102	24	18	6	12x14
28	50	110	24	18	6	12x14
30	54	114	24	18	6	12x14
32	58	121	24	18	6	12x14
34	62	131	24	18	6	12x14
36	66	137	24	18	6	12x14
38	70	155	24	18	6	12x14
40	72	159	24	18	6	12x14
42	76	163	24	18	6	12x14
44	80	167	24	18	6	12x14
46	84	184	24	18	6	12x14
48	88	188	24	18	6	12x14
50	82	192	24	18	6	12x14