

The Salo is a fusion of handcrafted rings which emit light from both the internal and external sides through hundreds of individually cut and hand laid faceted diffusers.

Standard profile size: 40x40mm.

Up to 8 tiers, from 40 to 230cm diameters.

Hanging Fully adjustable drop height on 1.2mm stainless steel suspension cables.

**Light Source** External and internal multifaceted clear diffusers. Integral LED lighting.

LED matrix, CRI>95, ~ 50K hours life.

LED standard colour temperature options: 2.7k and 3k (other

temperatures available on request) Power to fixtures: Via suspension cables.

Light Output: decorative lighting element only. Indicative Lumen level available on request.

**LED Driver** Triac Dimmable (5%-100%) as standard,

all dimming protocols available on request.

Wattage dependent on sizing.

Output Voltage: 24V.

Input Voltage: 110V-230V-277V, to be specified.

### **Maintenance**

Clean with smooth and dry cloth. Do not use any ammonia, solvents or abrasives. No user serviceable components. Contact Cameron Design House for further information.

Bespoke options and design service available. All fittings and installation instructions are provided.

Contact CDH for further technical details/downloads: technical@camerondesignhouse.com camerondesignhouse.com

# Salo





Ceiling Rose

Direct Attach

Salo Taso Standard dimensions:


70,100,90,80,60cm 28".40".36".32".24






#### Salo Elama

Standard dimensions: 60,80,100,50,70,40cm 24" 32" 40" 20" 28" 15





### Salo Lunar

Standard dimensions: From 50 to 120cm 20"-47



Ceiling Rose or Direct attach as standard. Download our "Standard hanging option" spec for further information. Custom option available.



Conforms to UL Std.: 2108

## Finishes and Materials Options - Size limitation for some finishes, contact CDH for a formal quotation.

Polished Metal

Brushed Metal













Full range of Ral Colours available