



BLUETOOTH

"BLTH": NEW BLUETOOTH INTERFACE FOR WEIGHT INDICATORS



Thanks to the BLTH interface, which may be built inside the weight indicator, the exchange of data between the portable PC or the PDA and the weight indicator will be simpler and quicker: one just needs to be at a few meters from the weight indicator in order to update the databases, read the memory, transmit commands, receive data, check the configuration, etc.

The best solution
for advanced industrial
applications

TECHNICAL FEATURES

- Standard: Bluetooth "version 2.0 +EDR"
- Class: 2
- Maximum working distance: 2m
- Transmission speed: 300kbps
- Supported Bluetooth profiles: Serial Port Profile (SPP)
- Antenna: integrated on the board
- Installation: integrated inside the weight indicator

NOTE: BLTH is an option to be specified when ordering the indicator or the scale.

SET OF COMMANDS AND COMMUNICATION PROTOCOLS

- The Dini Argeo weight indicators are fitted with a communication protocol for the data exchange, which allows the weight reading, the execution of the main scale functions and the programming of the databases (depending on the indicator model).



GRAVITATION LTD.

UNIT 2B SECTION 5 DUNSHAUGHLIN - - CO. MEATH - IRELAND

Tel. 00353469078900

Fax. 00353469078911

E-mail info@gravitation.ie

Web www.gravitation.ie

All the specifications and images can be subject to variations and upgrades without prior notice.