



PROFI 232

"PROFI232" EXTERNAL PROFIBUS INTERFACE IN CASE FOR DIN BAR,
FOR "ENTERPRISE" SERIES INDICATORS



External interface which allows to connect the CPWE and 3590E weight indicators to the Profibus networks. Wide range of available data.

The best solution
for advanced industrial
applications

FUNCTIONING

- Complete functionality from the Profibus-DP Slave, in according to IEC 61158
- 16 input bytes / 16 bytes output on SSC interface
- Automatic baud rate selection: from 9600 bit/s to 12Mbit/s
- Wide range of available data depending on the weight indicator to which it is applied
- Available for CPWE and 3590E indicators, in the versions with management of the Profibus protocol

TECHNICAL FEATURES

- ABS case for panel mounting on DIN bar
- Dimensions l x w x h (mm): 53 x 58 x 90
- Power supply: from 12 to 24Vdc
- RS232 and RS485 serial ports on terminal board
- Profibus port on 9 Pin connector
- Board optoisolation against electric or electrostatic discharges



GRAVITATION LTD.

UNIT 2B SECTION 5 DUNSHAUGHLIN - - CO. MEATH - IRELAND

Tel. 00353469078900

Fax. 00353469078911

E-mail info@gravitation.ie

Web www.gravitation.ie

All the specifications and images can be subject to variations and upgrades without prior notice.