



LCCB

"LCCB": CABLE for CONNECTION TO LOAD CELLS



Shielded cable for connection of weight indicators to load cells or junction boxes.

The best solution  
for advanced industrial  
applications

## LCCB cable features

- Type: 6 x 0,25 mm<sup>2</sup>.
- Built-in shielding for protection from disturbances.

<u>Dini Argeo standard of colour codes</u>	
<i>Colour</i>	<i>Function</i>
YELLOW	OUTPUT -
PINK	OUTPUT +
GREEN	SENSE +
WHITE	SENSE -
BROWN	INPUT +
GREY	INPUT -

## LCCBM cable features

- Indicated for applications with moving cables.
- Type: 4 x 0,34 mm<sup>2</sup>.
- Built-in shielding for protection from disturbances.

<u>Dini Argeo standard of colour codes</u>	
<i>Colour</i>	<i>Function</i>
YELLOW	OUTPUT -
GREEN	OUTPUT +
WHITE	INPUT -
BROWN	INPUT +

## DETAIL 1



LCCBM: shielded 4-pole cable for load cells.



GRAVITATION LTD.

UNIT 2B SECTION 5 DUNSHAUGHLIN - - CO. MEATH - IRELAND

Tel. 00353469078900

Fax. 00353469078911

E-mail [info@gravitation.ie](mailto:info@gravitation.ie)

Web [www.gravitation.ie](http://www.gravitation.ie)

*All the specifications and images can be subject to variations and upgrades without prior notice.*