



OBRF3GD

"OBRF3GD": RADIO FREQUENCY INTERFACE BOX FOR ATEX 2 and 22 ZONES



Radio frequency module for the wireless data communication in ATEX 2 and 22 zones, with protection methods according to:
ATEX II 3G Ex nA IIC T6 Gc X for gases
ATEX II 3D Ex tc IIIC T125°C Dc IP66 X for dust.
It can be applied to both bench/floor scales as well as mobile scales, such as pallet truck scales or pallet weighing scales, and it allows to transmit data at a very long distance.

The best solution
for advanced industrial
applications

Technical features

- IP66 ABS case.
- Dimensions case (lwxh): 120x80x55mm.
- Fitted with 3m shielded cable, for connection to the indicator.
- Power supply directly from the indicator.

Operating features

- Work frequency from 868 to 870 MHz, which reduces the risk of interferences with the classic radio frequency systems.
- Up to 50 different channels, easily programmable with the programme on PC, in order to install various independent systems in the same work area.
- Max. functioning distance, in appropriate environmental and installation conditions: up to 70m indoors, and up to 150m outdoors.
- Does not require particular communication protocols, transmission in transparent manner of any character received in input.



GRAVITATION LTD.

UNIT 2B SECTION 5 DUNSHAUGHLIN - - CO. MEATH - IRELAND

Tel. 00353469078900

Fax. 00353469078911

E-mail info@gravitation.ie

Web www.gravitation.ie