

TPWLK

TPWLK "LOGISTIC" SERIES PALLET TRUCK SCALE



Pallet truck scales, with built-in electronic weighing, which are reliable, easy to use, suitable for harsh work conditions. These are essential for one who needs to weigh accurately but save time also. Fitted with rechargeable extractable battery. Available also with a built-in printer as well as CE-M DOUBLE RANGE approved.

The best solution
for advanced industrial
applications

MAIN FEATURES

- Maximum lifting capacity: 2000 kg.
- Accuracy: +/- 0.1% of the maximum capacity in the versions for internal use.
- Accuracy: +/- 0.05% of the maximum capacity in the "M" approved versions.
- Fork dimensions 1150 x 550 x 85 mm.
- Weighs about 125 kg.
- Structure in extra thick steel and oven-fire painted mechanics.
- Steering wheels and double loading poliurethane rollers.
- 4 stainless steel IP68 load cells for the legal for trade use version, aluminium IP54 load cells for the internal use version.
- Weight indicator in IP65 STAINLESS STEEL waterproof case, easy to clean and resistant to harsh and corrosive environments; large 25mm LCD display high contrast digits, which are clearly visible even in poor lighting conditions and with low temperatures, and waterproof membrane keyboard, with 17 functional keys.
- Configuration, calibration and diagnostics from keyboard or PC with DINITTOOLS.
- Power supply through extractable rechargeable battery mounted on the pallet truck column.
- The operating time is of about 80 hours of continuous use or one month with the tipycal non continuous use, thanks to its auto switch-off function.
- Programmable auto power saving function.
- Battery level indication.
- Equipped with 230Vac 50 Hz battery charger (recharging time is about 8 hours).
- Configurable RS232/C bidirectional port for connection to a printer, with customisable print format.
- Configurable RS232/C bidirectional port for PC, modem radio or portable terminal.
- IR input for remote control management.
- Fitted with thermal printer in the TPWLKP and TPWLKPM versions, with Date&Time card.

MAIN FUNCTIONS

- Zeroing, Tare, Printing
- High Resolution Weighing x 10
- Net/Gross or lb/kg conversion
- Accumulation
- Formulation
- +/- Checkweighing
- Percentage weighing
- Counting (Max. resolution of 1.500.000 divisions)
- Hold and Peak
- Set Point Control (with optional interface)

AVAILABLE UPON PRICE ESTIMATE

- Special steering wheels.
- 680 mm fork width.
- Special fork length from 850 to 1500 mm.
- Special capacity e/o divisions.
- High resolution.

VERSIONS

Versions available

Code	Max (kg)	d (kg)	M (kg)
TPWLK-3	500 / 1000 / 2000	0,2 / 0,5 / 1	
TPWLKM-3 M	1000 / 2000		0,5 / 1
TPWLKP-3	500 / 1000 / 2000	0,2 / 0,5 / 1	
TPWLKPM-3 M	1000 / 2000		0,5 / 1

Please take note that the column and the handle-bar require assembly.



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI AR GEO
FRANCE sarl
Nogent-sur-Marne
info.fr@diniargeo.com

DINI AR GEO
GMBH
Sinsheim - Germany
info.de@diniargeo.com

DINI AR GEO
UK Ltd
Taunton - United Kingdom
info.uk@diniargeo.com

DINI AR GEO WEIGHING
INSTRUMENTS Ltd
Shanghai - China
info.cn@diniargeo.com

DINI AR GEO
WEIGHBRIDGES
Calto (RO) – Italy
info@diniargeo.com




HEAD OFFICE

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 843418 Fax. +39.0536 843521
info@diniargeo.com

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 921784 Fax. +39.0536 926654
service@diniargeo.com



SALES AND TECHNICAL ASSISTANCE SERVICE