

TPWP

TPWP "PROFESSIONAL" SERIES PALLET TRUCK SCALE



Pallet truck scales, with built-in electronic weighing having very high performance. The four load cell weight detection guarantees the best accuracy. Reliable and suitable for one who needs to weigh accurately any type of product on a pallet. Available also CE-M APPROVED.

MAIN FEATURES

- Maximum lifting capacity: 2500 kg.
- Accuracy: +/- 0.05% of the maximum capacity.
- Fork dimensions 1150 x 550 x 85 mm.
- Weighs about 125 kg.
- Bearing structure in extra thick sheet steel and oven-fire painted interior construction.
- Standard fitted swivelling column head.
- Steering wheels and double loading rollers with a poliurethane coating.
- 4 stainless steel IP68 load cells.
- Indicator with easy to clean ABS waterproof IP65 case enclosure built to withstand humid and dusty environments; large LCD display with 25 mm high contrast digits, which are clearly visible even in poor lighting conditions; 17-key numerical/functional membrane waterproof keyboard.
- Calibration and Set-Up configurable from keyboard or from PC with DINITOOLS.
- Power supply through built-in extractable rechargeable battery.
- 60-hour approximate operating time or three months with the typical non continuous use, thanks to its auto switch-off function.
- Programmable auto power saving function.
- Low Battery Warning.
- Equipped with 230Vac 50 Hz battery charger (recharging time is about 8 hours).
- Bi-directional RS232/C port configurable for connection to printer.
- Bi-directional RS232/C serial output for radio modem, PC or portable terminal.
- IR input for managing the remote control.

MAIN FUNCTIONS

- Zeroing, Tare, Printing, numeric IDs
- High Resolution Weighing x 10
- Net/Gross or lb/kg conversion
- Accumulation
- Formula weighing
- +/- Checkweighing
- Percentage weighing
- Counting (Max. resolution of 1.500.000 divisions),
- Hold and Peak
- Set Point Control (with optional interface)

AVAILABLE UPON PRICE ESTIMATE

- Special steering wheels.
- 680 mm fork width.
- Special fork length from 850 to 1500 mm.
- Special capacity e/o divisions.
- · High resolution.

VERSIONS

Available versions				
	Max	d	M	d* HR
Code	(kg)	(kg)	(kg)	(kg)
TPWP25D	600 / 1500 / 2500	0,2 / 0,5 / 1		0,1 / 0,2 / 0,5
TPWP15DM	600 / 1500		0,2 / 0,5	
TPWP25DM	1500 / 2500		0,5 / 1	

^(*) The HR division is obtainable only with the relative EHR option



GRAVITATION LTD.

UNIT 2B SECTION 5 DUNSHAUGHLIN - - CO. MEATH - IRELAND

Tel. 00353469078900 Fax. 00353469078911 E-mail info@gravitation.ie Web www.gravitation.ie