

XTRABOND[®]HT

HIGH-TEMP RTV SILICONE SEALANT



PRODUCT DESCRIPTION:

XtraBond[®]HT is a one part, easy to use, non-slumping paste that cures to a silicone rubber when exposed to atmospheric moisture at room temperature. This product is engineered to provide a durable, watertight bond when exposed to continuous temperatures ranging from -40° to 500°F – while maintaining its integrity at up to 600°F for intermittent time periods. Its unique formulation acts as both a thermal and electrical insulator as well, so it is ideal for sealing around heating elements.

USES:

XtraBond[®]HT can be used for a variety of applications including, but not limited to, Sealing around heating elements, Furnace Vent Pipes, Industrial Ovens, Smoke Stacks, Engine Parts, Fireplaces, HVAC, etc.

DIRECTIONS FOR USE:

For best results, prepare a clean surface. Cut nozzle to desired bead size. Apply with caulking gun, forcing sealant onto the substrate, then tool if needed. Clean excess material with mineral spirits or similar solvent.

SURFACE PREPARATIONS:

The substrate must be clean, dry, frost free, sound, and free of any oils, grease or incompatible sealers, paints or coatings that may interfere with adhesion. Do not apply if surface is damp or contaminated. It is recommended all substrates are tested prior to application. Primers are not required for most substrates.

STORAGE:

Be sure to rotate inventory accordingly. Materials must be properly stored in a low humidity (<50% RH) environment at room temperature (73 ± 2°F) in their unopened container. Cartridges/Sausages, use within 18 months from date of manufacture. Pails/Drums, use within 12 months from date of manufacture.

Weather Defense System

This XtraBond[®] product is a part of the XtraGuard Weather Defense System[™], an integrated product line of building components developed from advanced materials research that increase the durability and comfort of residential and commercial structures by effectively managing moisture. The product's aggressive adhesion and compatibility with all major building materials makes it a critical link in the XtraGuard Weather Defense System, when combined with the company's complete line of Wraps and Flashing Products.

FEATURES:

- Approved in High Temperature Areas
- Non Sag Red Formula
- Insulates Electrically
- Up to 600°F
- Insulates Thermally
- Non-Sag

COLORS:

Red



CHEMICAL & PHYSICAL PROPERTIES

Skin Time	Internal Method	< 20 minutes @ 70°F / 50% RH
Tack Free Time	Internal Method	< 30 minutes @ 70°F / 50% RH
Cure Rate	Internal Method	1/4" Bead in 24 Hours
VOC	EPA Method 24	< 23 g/L, less water and exempt solvents
Elongation @ Break	ASTM D412	400 - 450%
100% Modulus of Elasticity	ASTM D412	50 - 75 psi
Shore A	ASTM C661	25 ± 5
Movement Capacity	ASTM C719	± 25%
Tensile Strength	ASTM D412	180 - 250 psi
Staining	ASTM D2203	None
Sag/Slump	ASTM D2202	Minimal; < 0.2"
UV Rating	ASTM G154	No discoloration or change in appearance after 2500 hours
Service Temperature	Internal Method	-40 - 500°F
Density	Internal Method	Approx. 8 lbs./gal
Percent Solids	Internal Method	> 96%

Specifications: XtraBond®HT meets or exceeds the requirements of NSF/ANSI 51 - Food Equipment Materials. ASTM C920 Type S, Grade NS, Class 25, Use NT, G, M, A. Federal Specification TT-S-00230C Type II, Class A, TT-S-001543A Type Non-Sag, Class A.

APPROXIMATE* LINEAR FEET/COVERAGE PER 10.1 FL. OZ. CARTRIDGE (298 ML)

DEPTH	WIDTH							
	1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
1/8"	99	49	33	24	20	16	14	12
1/4"		24	20	12	10	8	7	6
3/8"			11	8	6	5	5	4
1/2"				6	5	4	3	3

*All values are approximations based upon industry information and can vary dramatically due to joint dimensions/configurations, porosity, texture of substrates, irregularities, installation techniques, waste, etc. that are beyond Premier Building Solutions' control. Premier Building Solutions is not liable for variances to linear feet/coverage; do a test area to determine material required to use.

LIMITED LIFETIME WARRANTY:

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Building Solutions, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

Premier Building Solutions specifically disclaims and makes no warranties, express or implied, about this product, its merchantability, or its fitness for a particular purpose. All recommendations, directions, and suggestions for its use are consistent with our testing and research for a variety of applications, but no promises, guarantees, or warranties are being made with regard to its use, whether or not consistent with the directions, or its effectiveness for any given application. Users of this product should do so in compliance with all applicable laws and regulations. User of this product should conduct its own field test, to assure results.

191204-PBS-XBHT-Ver8

Green Advantage Program

This XtraBond® product is a part of Premier's "Green Advantage" Program – the designation of our commitment to not only superior products & services, but also the environment. Our engineering formulations, manufacturing standards and production practices allow us to be a leader in the supply of eco-friendly and VOC compliant products. Learn more at www.PremierBuildingSolutions.net/green

Who is Premier?

This XtraBond® product is manufactured and distributed by Premier Building Solutions, a manufacturer of high performance systems that provide protection in commercial and residential buildings – as well as a variety of other industrial and transportation applications.

The company's history of innovation has led to the development of breakthrough adhesive chemistries and new industrial-strength products that help customers increase the efficiency and durability of their critical assets.

PACKAGING



CARTRIDGES



DRUMS