

HEAVY DUTY SERIES

Turbo Gas Fryers



The images presented here are illustrative and may vary or not exactly match the physical product.









DESCRIPTION

Coriat Heavy Duty Series Turbo Gas Fryers are specially designed as central elements in regular kitchens or as auxiliary devices in very large kitchens. They are perfect for large volume production of french fries, onion rings, tenders, wings and seafood.

SPECIFY TYPE OF GAS WHEN ORDERING

Natural	Gas

Propane

SPECIFY ALTITUD

Above 2,000 ft

TOJECT		
ΔΙΑ#	SIS#	
tem#_	 Quantity	

MODELS

TURBO 25.5-4Q
TURBO 30-50

STANDARD FEATURES

- External and internal sheet metal parts in stainless steel.
- 16 gauge stainless steel tank.
- Cold zone that extends oil life.
- Nickel plated baskets with plastic coated handles.
- 23,000 Btu/h cast burners.
- Snap action thermostat, 212 400°F (100 - 204°C) temperature range.
- Safety millivolt valve.
- Automatic high temperature limit control, calibrated to 450°F (232°C).
- Cold zone that extends oil life.
- 1 1/4" Ø ball type drain valve.
- Gas pressure regulator.
- Stainless steel adjustable legs.
- CSA design certified, NSF listed.

Approved by	Date	Approved by	Date





HEAVY DUTY SERIES


Turbo Gas Fryers

CLEARANCE AND POSITIONING REQUIREMENTS

This product must be installed on a non-combustible surface only, with a minimum of 6" from all sides. There must be a clearance of at least 6" from another appliance. This unit is supplied with 4 legs and must be placed on a resistant non-slip surface.







Model	Width (A)	Depth	Overall Height	Working Height	Tank Size	Fry Capa- city (lbs)	BTU/HR	Shipping Weight (Lbs/Kg)
TURBO 25.5-4Q	19 1/8″	34 7/8"	46 1/2"	37"	17 1/8" X 14"	50	120,000	203/92
TURBO 30-5Q	22 1/4"	34 7/8"	46 1/2"	37″	20 3/8 X 4"	65	150,000	225/102

Constant improvement in all our processes is a Coriat value, therfore some specifications are subject to change without notice.

Approved by ______ Date _____ Approved by _____ Date _____