

Product: **SONAX ProfiLine Perfect finish**

Article Code: **224 000/ 141 /300 /500**

Formula Code: 2090 2555

Product Description: Silicone free finishing polish for professionally polishing of sanded down paintwork, or paintwork pre-polished with polishing machine and abrasive polish. Specially developed for paintshops, for 1-.step polishing of sanded down paint due to paintwork damage such as dust occlusion or paint runs. The special nano-abrasives enable effective scratch removal with optimum shine and without inducing holograms or buff marks on the paintwork.

Cut: 4
Gloss: 6

Directions for Use:

- Shake bottle/tube before use.
- Deep scratches or paintwork damage should first be wet sanded ..with abrasive paper P2000, or finer.
- Product to be worked in with a rotational speed regulated polishing ..machine.
- Apply a little of the product directly to the sanded spot.
- Polish the area at the lowest rotational speed (ca. 800 rpm) with the green Polishing pad (493 000) for 10 sec. Tilt the machine a little bit.
- Afterwards, increase to medium rotational speed and allow the machine to run, now exerting only moderate pressure.
- Guide it swiftly over the surface to avoid heat developing beneath the polishing pad.
- Remove polish residue with a microfibre cloth.

Please Note:

In some cases it may be sensible to use a lambskin.
To achieve a hologram-free finish on darker paintwork, finish polishing with a foam pad may be necessary.

Chemical Classification: Emulsion based on deodorized petroleum, with aluminium oxide as abrasive. Contains no silicones or waxes.

Specific Data:

Appearance:	White fluid
Density:	1.12 – 1.13
Viscosity:	15– 25 Pas (Brookfield Sp. 6. 20 rpm)
pH:	9.0 – 9.5

Packaging:

75 ml PE-tube	(224 000)
250 ml PE/PA bottle	(224 141)
1 Ltr. PE/PA bottle	(224 300)
1 Ltr. PE-canister	(224 500)

Safety Data: See safety data sheet