

Product: SONAX ProfiLine Ex-Cut 05-05

Article Code: 245 141/300/500

Formula Code: 2460 0017

Product Description: Abrasive paste for orbital machine processing. For processing

scratched or locally sanded paint layers. Eradicates deep scratches as

well as corrosion due to bird droppings, insects and tree sap.

Cut: 5 Gloss: 5

Directions for Use: - Shake container before use.

- The product is to be used with an orbital polisher with rotational speed regulator. The red Cut pad is the recommended polishing

sponge. The lambskin is also an option.

- Apply a little product directly onto the area to be treated or the

sponge.

- Polish for a few seconds at a low rotational speed, then polish out at

maximum rotational speed exerting moderate pressure.

- Remove polish residues with a microfibre cloth. Check the polishing area and, if necessary, carry out a further polishing step with new

material.

Please Note:

With fresh paintwork two short polishing steps each using little material are better than one extensive process with lots of polish.

Chemical Classification: Emulsion based on dearomatised benzene with aluminium oxide as

abrasive. Silicone and wax free.

Specific Data: Appearance: white fluid

Density: 0.97 – 0.99 g/ml

Viscosity: 15 – 30 Pas (Brookfield Sp. 7, 20 rpm)

pH: --

Packaging: 250 ml PE/PA bottle (245 141)

1 ltr. PE/PA bottle (245 300) 5 ltr. PE canister (245 500)

Safety Data: See safety data sheet

Source: 1techdat\datenblaetter\ Date: 05.12.16 Printed: 29.04.21 File: 245141e.docx Made by: EF/ M. Pitsch Revision: 0