

Product:	SONAX ProfiLine Cut Max	
Article Code: Formula Code:	246 141/300/500 2460 0017	
Product Description:	partially sanded painty abrasions and remove from P1000 grain size Dust Technology.	
Directions for Use:	 Wash vehicle thoroughly and wipe dry. A polishing machine with variable rotational speed and with red Polishing sponge 160 (hard) is recommended or, alternatively, the Lambskin pad 130. Guide the polishing machine initially at low rotational speed (800 rpm), exerting somewhat higher pressure, then reduce pressure and for polishing out, press the machine lightly in the process increasing to a medium rotational speed (1500 rpm max.). This will attain an even higher gloss level. Remove polish residues completely with a microfibre cloth. To improve the gloss level on the treated area, polish it once again with SONAX Perfect finish or SONAX EX 04-06 in case of use of a DA- polisher. 	
	 Please Note: Do not apply in direct sunlight or onto warm surfaces. Protect against extreme cold. Do not polish a smaller area for too long, as there is a danger of producing a polishing spot or even polishing through the lacquer. 	
Chemical Classification:	Emulsion containing abrasives, silicone free, wax free.	
Specific Data:	Appearance: Density: Viscosity:	White, viscous fluid 0.99 – 1.01 g/ml 15 – 20 Pas (Brookfield Sp. 6/20 rpm)
Packaging:	250 ml PE/PA bottle 1 L PE/PA bottle 5 L PE canister	(246 141) (246 300) (246 500)
Safety Data:	See safety data sheet	