

Product: SONAX Clay

Article Code: 450 205

Formula Code -

Product Description: Soft abrasive clay for removing stubborn dirt from painted car

components that can't be removed in the car-wash (industrial fallout,

tree sap, tar, insect residue, industrial dust, spray paint mist).

Directions for Use: - Wash the car thoroughly to avoid unnecessary scratches caused by

stray sand grains. Do not chamois dry!

- Spray SONAX Glass clear onto the areas requiring treatment, this creates a sliding film between the clay and the painted surface.

- Applying slight pressure, guide the clay in circular movements over the dirty areas until no more unevenness can be felt. The abraded

dirt particles are absorbed into the clay.

- If the clay surface is saturated with dirt, form the clay into a new,

clean working surface.

- Wipe the painted surface clean with a microfibre cloth.

- When the work is finished, the clay should be stored in the box so

that it does not dry out.

Notice:

After the treatment it is advisable to polish the paintwork, as, in many cases, underneath the surface dirt the paintwork is being attacked.

Chemical Characterisation: Compound of clay and calcium carbonate in polyolefine

Specific Data: Appearance: Blue clay

Density: 2.5 g/cm³ Weight: ca. 200 g

Dimensions: 90 x 55 x 20 mm

Packaging: PE-Box

Safety Data: See safety data sheet

Source: 1techdat\datenblaetter\ Date of issue: 13.10.05 Date of print: 29.04.21 File Name: 450205e.doc Author: EF/ R. Hanauer Revision: 0