

Product: SONAX SX 90 Easy spray

Article Number: 474 100 / 400/541

Formula Number: 4740 0392

Product Description: The universal trouble shooter for car, household, hobby or workshop.

Lubricates, loosens jammed connections and eradicates squeaking and creaking noises. Contact spray for ignition systems. Can also be used for the cleaning and maintenance of precision engineered machines and equipment. The transparent and odour neutral protective film lastingly protects bare metal parts against corrosion. Dissolves and removes tar, adhesive residues and labels. The new and innovative spray nozzle enables both a targeted pinpoint application of small amounts, as well as extensive spraying of larger

quantities.

Directions for Use: - Shake can before use.

- Spray on SX 90 Plus as a thin film.

- When working on electrical equipment, disconnect the power supply and allow the product to ventilate for ca. 2 minutes before resuming

operation.

- Can is sprayable from any angle due to a special valve.

Chemical Classification: Rust inhibitor, lubricant, and cleaning additive in mineral oil

Propellant Gas: Propane/butane

Specific Data: Appearance: Opaque fluid

Density: 0.835 – 0.845 g/ml

Viscosity: 12 – 15 s (Ford cup 4mm)

Operating temperature: $-10 \, ^{\circ}\text{C} \rightarrow +200 \, ^{\circ}\text{C}$

Packaging: 100 ml Aerosol spray (474 100)

400 ml Aerosol spray (474 400) Counter display (474 541)

Safety Data: See safety data sheet

Source: 1techdat\datenblaetter\ Date: 09.09.2020 Printed: 29.04.2021 File: 474100e.doc Made by: EF/ M. Pitsch Revision: 2