

**Product:** SONAX Foam Pad hard 160

**Art. No.:** 0493 1000

**Formula No. :** -----

**Product Description:** Polishing Pad for polishing machine. Hard and open-porous sponge for the polishing of weathered or scratched paints. Hook & Loop system for quick pad change. Ideal for effective application of all SONAX abrasive polishes. It is relatively rigid and passes the pressure from the polishing machine onto the to be polished paintwork very well. The foam has relatively large cells and stable connectors.

**Application:**

- Place pad centrally onto the back-up plate (Art.No. 493 200) to achieve a smooth run.
- Do not use high revs to avoid heating up the paintwork and to minimize swirl marks.
- Moisture the surface if necessary to elongate the polish time

**Please note:**

- Lifetime of the sponge can be significantly increased when the polish is washed out regularly by hand with warm water. Never use a high pressure device!
- Never use this sponges together with other polishes for finishing works, rests of the abrasive polishes may cause hologramms

**Composition:** solid polyurethane foam with open celled structure.

**Specific data:**

|                       |                         |
|-----------------------|-------------------------|
| bulk density:         | 36-42 kg/m <sup>3</sup> |
| number of cells:      | 14-18 c/cm              |
| compression hardness: | 20kPa                   |

**Packaging:** ---

**Safety data:** ---