Commonly used throughout North America · Backed by a one-year manufacturer warranty

Product Specifications:

- Die cast aluminum, will not rust, 100% recyclable
- Vibratory polished to a low sheen
- Set screw or bolt thru sign mounting

Testing Specifications:

- Post mounting fasteners tested at 100 in-lbs torque
- Sign mounting fasteners tested at 50 in-lbs torque
- Tested with grade 2 fasteners
- Fatigue tested to 100,000 cycles



5-UX90 Fastener Options 'ZP' = Zinc Plated / 'SS' = Stainless Steel 5-UX90 • includes no fasteners (we can even offer fasteners not listed in our catalogue)	
• SCKT SET SCREW, 5/16"-18UNC X 0.375", KNRLD, 5/32" HEX (x2)	• HEX HEAD BOLT, 5/16"-18UNC X 0.5" (x2)
● HEX HEAD BOLT, 5/16"-18UNC X 0.75" (x2)	• HEX HEAD BOLT, 5/16"-18UNC X 0.75" (x2)
5-UX90-ZPV / 5-UX90-SS	5-UX90-ZPVB / 5-UX90-SSVB
• SCKT SET SCREW, 5/16"-18UNC X 0.375", KNRLD, PIN-IN, 5/32" HEX (x2)	• BUTTON HEAD BOLT, 5/16"-18UNC X 0.75", PIN-IN, 5/32" HEX (x4)
● BUTTON HEAD BOLT, 5/16"-18UNC X 0.75", PIN-IN, 5/32" HEX (x2)	



dynaengineering.com