



72V 105Ah

Voltage: 76.8V | Capacity: 105Ah | Energy: 8064Wh

ELECTRICAL SPECIFICATIONS

| | |
|-----------------------------|----------------|
| Nominal Voltage | 76.8V |
| Nominal Capacity | 105Ah |
| Bluetooth Enabled | Yes |
| Capacity @ 20A | 400 min |
| Efficiency | 99% |
| Self Discharge | 1-3% per month |
| Maximum Modules in Parallel | 2 |

MECHANICAL SPECIFICATIONS

| | |
|------------------------|-----------------------|
| Dimensions (L x W x H) | 25.9" x 13.6" x 9.75" |
| Weight | 157 lbs |
| Terminal Type | M8 |
| Terminal Material | Brass |
| Case Material | Steel |
| Enclosure Protection | IP67 |
| Cell Type - Chemistry | Prismatic LiFePO4 |

DISCHARGE SPECIFICATIONS

| | |
|-------------------------------|----------------------|
| Max Continuous Current | 180A |
| Peak Discharge Current | 350A (10s) |
| Peak Instantaneous Current | 500A (<1200ms) |
| Low Voltage Disconnect | 60V |
| BMS Discharge Voltage Cut-Off | 60.0V (2.5±0.05 vpc) |
| Reconnect Voltage | 67.8V (2.8±0.1 vpc) |
| Short Circuit Protection | 200-400ms |

BLUETOOTH FEATURES

| |
|--|
| Voltage (overall and individual cell voltages) |
| Remaining Discharge Time |
| Remaining Charge Time |
| Current Amp Draw |
| Current Cell Temperature |
| Voltage of Individual Cells |
| Lifetime Power Cycles |

CHARGE SPECIFICATIONS

| | |
|--------------------------------|-----------------------|
| Recommended Charge Current | 15A - 50A |
| Discharge Temperature | 15° to 140°F |
| Temperature Protection Release | Low: 23°F High: 122°F |
| Charge Temperature* | 32° to 131°F |
| Recommended Charge Voltage | 60V - 88.8V |
| BMS Charge Voltage Cut-Off | 93.6V (3.75±0.05vpc) |
| Reconnect Voltage | 92.4V (3.55±0.05vpc) |

KEY FEATURES

| |
|---|
| 2 Amp Internal Balancer (80 times faster) |
| BMS languages - CANbus & RS485 |
| Sleep Mode |
| Fire Arrestor |
| Thick Steel Casing |

SAFETY SPECIFICATIONS

ALL VISIBLE ON THE ALLIED BATTERY BLUETOOTH APP

| | |
|------------------------------------|--|
| Short Circuit | Yes |
| Low / High Temperature Discharging | Yes |
| Low / High Temperature Charging | Yes |
| Over-Current Discharging | Yes |
| Over-Current Charging | Yes |
| Pack Under / Over Voltage | Yes |
| Certifications | UL1642 IEC62619 (Cells) CE UN38.3 (Battery) |
| Shipping Classification | UN 3480 Class 9 |

DIMENSIONAL SPECIFICATIONS

