



Offering more



**RIPACK**® SERIES 3000



[www.ripack.com](http://www.ripack.com)



## SAFE

Prevent any burn risks and work in complete safety. With its unique, patented **cold nozzle** system, the gun remains cool during use.

Non-stop rotation of the nozzle possible with bare hands



## PRACTICAL

Large, solid hanger ring.

Easy to attach on RIPACK® gas cylinder trolleys



## FAST

Save 15% of your time thanks to its increased power.

By covering an even larger surface area, shrinking operations are much faster and more consistent.

Film 120µ

↑ H

⌚

→ 2,00 m = 110 sec

→ 1,50 m = 80 sec

→ 1,00 m = 50 sec



## SECURIPACK

In the event of hose damage or low gas supply, **two safety mechanisms** in the regulator cut the gas flow and guarantee **the nozzle remains cold**.



The peripheral suction holes allow for a constant air flow under any conditions.



## COMFORTABLE

Dual-material ergonomic handle for improved control. The rotating connection eases hose self-alignment during gun movement.

## ROBUST

Its body is made from **die-cast aluminium** and its nozzle is made from **stainless steel** to insure meeting the conditions of a **reliable and long-lasting product**.





**+ ERGONOMIC**  
The pivoting arm rest provides increased comfort during use with an extension wand and folds away after use for storage.



**Fully rotatable nozzle**

**+ SMART**

RIPACK® SERIES 3000 is delivered in a footstool carrying case capable of supporting the weight of an operator max. 120 kg (265 lbs). This eases the storage and transport of common accessories.



**MODULAR**

With a range of easily interchangeable extensions the RIPACK® SERIES 3000 can be extended to 2 metres (6.8 feet), so is suitable to all applications from pallet wrapping to buildings containment.

**+ SMART**

The trigger opening enables you to quickly change the igniter. An Allen key is provided for removing the trigger if required.



**+ PRODUCTIVE**  
Say goodbye to production downtime. A reserve igniter is stored in the trigger guard casing and its tool-free changeover can be carried out in less than a minute.



# Ensure that **YOUR PRODUCTS ARE SAFE**

under any

conditions

- instability
- shape
- transport
- storage



















exposure

- climate
- corrosion
- abrasion

risks

- theft
- sagging
- customer complaints
- degradation

Benefit from the versatility of the **RIPACK® SERIES 3000**

Packaging	Marine	Bulk items	Containment	Marking	Miscellaneous
 <p>Pallet containing glassware</p>	 <p>Over-wintering of recreational boats</p>	 <p>Machines with non-standard dimensions</p>	 <p>Temporary covering spaces</p>	 <p>Application of thermo-plastic road markings</p>	 <p>Flame-treating parts</p>
 <p>Heavy, fragile and/or unstable loads</p>	 <p>Land storage in a marina</p>	 <p>Public works, rolling stock</p>	 <p>Containment for asbestos removal</p>	 <p>Playgrounds</p>	 <p>Thermal weed control</p>
 <p>Irregularly shapes palletised and non-palletised loads</p>	 <p>Shipyards</p>	 <p>Aeronautics industry, military ...etc</p>	 <p>Protecting a worksite against weather conditions</p>	 <p>Various instructional ground markings</p>	 <p>Adhesive label removal</p>



The film takes on the shape of the product by shrinking under the heat produced by the RIPACK® SERIES 3000. The film forms an excellent protective layer and thermal barrier. The objects are held together and the heat transferred is minimal.

## Adopt **SHRINKWRAP**

Low-density polyethylene (LDPE) is the most common form of shrink wrap film and is available in roll, tube and sheet configurations to suit all applications. Film can be produced in a choice of thickness, opacity and colours to match a shipper's specification.





### RIPACK® SERIES 3000 CARRYING CASE

To facilitate wrapping of pallet loads, the carrying case also acts as a 27 cm (10 inch) high step stool with a maximum loading of 120 kg (265 lbs).

Dimensions : L x l x H : 512 x 292 x 270 mm

Total weight when full : 5020 g

This product was eco-designed to reduce its environmental impact.

The holding quality and protection offered by the shrinkwrap reduces the number of intermediary wrapping operations normally required. No more need to overwrap/strap products to secure goods, thus reducing excess consumption.

The plastic used for shrink wrapping can be recycled and reused as a component in new films or to manufacture plastic bags or agricultural plastics.



### MOBILE SHRINKWRAP STATION

RIPACK® trolleys are available in two versions for the easy movement of capacity gas cylinders 13 kg (29 lbs), 19 kg (42 lbs) and 33 kg (73 lbs). The hose is protected and elevated by a flexible or articulated mast (depending on the model selected) to guarantee longer product life, greater operator comfort and compliance with safety regulations.

### STATIONARY SHRINKWRAP STATION

The RIPACK® retractable hose reel is both wall-mountable and free-standing and includes a 13 m (42 ft.) hose for improved access to areas around one or several pallets. Its steel drum construction and ratchet mechanism ensure reliable and comfortable operation.



### The case contains :

- 1 RIPACK® SERIES 3000 including one rotating connector and two piezo igniters (one reserve for emergency back-up purposes)
- 1 Securipack - combined fail-safe regulator
- 8 meter (26 ft) hose protected from abrasion, provided with mounted connectors
- 1 combination spanner for fitting gas connectors
- 1 instruction manual
- 1 year warranty (5 years for the aluminium body)

All information and photos provided in this brochure originate from an update performed on 09/2012. RIPACK® reserves the right to modify the colors, materials, properties and specifications of its models at any time. Some models may be assembled with accessories and/or properties that are unavailable in some countries. All rights reserved. The reproduction of this document, whether in part or in full, in any form and by any means whatsoever, is forbidden without prior authorisation from RIPACK®.

### RIPACK® SERIES 3000 - Technical specifications

Adjustable power output	45 to 76 KW	153 000 to 260 000 btu/h
Pressure	1,5 to 3,5 bars	21 to 50 PSI
Length / Height	375 / 262 mm	14.84 / 10.31 inches
Net weight	1220 g	2.7 lb
Noise level	< 85 dbA	
Energy source	Propane ( natural gas upon request )	
Available accessories :		



RIPACK® in the world :

