

## Iso-Grip Vibration Isolator Car Camera Suction Mount (CM-ISGP-01)

---

### Assembly Manual



### What's In The Box

Please inspect the contents of your shipped package to ensure you have received everything that is listed below.



---

All rights reserved.

No part of this document may be reproduced, stored in a retrieval system, or transmitted by any form or by any means, electronic, mechanical, photo-copying, recording, or otherwise, except as may be expressly permitted by the applicable copyright statutes or in writing by the Publisher.

## Iso-Grip Vibration Isolator Setup

- Remove the black dust covers of the Suction Car Mount.



- Open the quick lock lever manually, as shown in the image.



- Place your first suction cup on selected position where you want to shoot and Mount the suction cup gripper on a flat surface, as shown in the image.



- Press the lever of the Suction Cup Gripper and lock it properly.



**NOTE:** It has three powerful suction cups that grip like glue on any non-porous surface and firmly hold your setup when moving at high speeds.



- Loosen the quick lock, set the position according to your setup requirement, and tighten it properly.

**NOTE:** Its three articulating arms let you position your camera gimbal set up at practically any angle.



- Place the DJI-QR Plate onto the Suction Car Mount.



- Then insert an Allen CSK Bolt and tighten properly using a 4mm Allen key.



- Follow the same process on the other Allen CSK Bolt.



- Loosen the knob of the DJI-QR Plate.



- Slide the DJI-Ronin Gimbal (**Not Included**) into the plate and secure it with the knob of the QR Plate.



- NOTE:** If the QR Plate is loose, tighten its bolt properly using a 2.5 mm Allen Key.



- Here is proper assembled image of Suction Car Mount & mount. your DJI-Ronin Gimble (Not Included) of your choice as shown.

**NOTE:** You can use the wires in different configurations depending on the load capacity of your setup.



**NOTE:** It has wire cable blocks that absorb inertial movements and support a 3-10 kg / 6-22lb heavy payload; Use these blocks in different configurations to precisely achieve the lift needed.

### Load Adjustment, Removable Cables & Tie-Down Blocks



**YOUR PROAIM ISO-GRIP VIBRATION ISOLATOR CAR CAMERA SUCTION MOUNT  
ALL DRESSED UP AND READY TO GO!**



(SHOWN WITH OPTIONAL ACCESSORIES)

**Warranty:** We offer one year warranty for our products from date of purchase. Within this period of time, we will repair it without charge for labor or parts. Warranty doesn't cover transportation costs nor does it cover a product subjected to misuse or accidental damage. Warranty repairs are subjected to inspection and evaluation by us.

**Liability:** We are not liable for damage caused by products that we do not supply or from mishandling in transit, accident, misuse, neglect, lack of care of the product, or service by anyone other than our company.

**Contact Us:** In case of any kind of dissatisfaction, please Contact us immediately and we promise our utmost support and care until you use our product.