

Trailer Hitch Adapter/Tow Bar (P-THA)

Assembly Manual



What's In The Box

Please inspect the contents of your shipped package to ensure you have received everything that is listed below.



Proaim Trailer Hitch Adapter/Tow Bar



1 x 42.4 mm Speed Rail
Pipe Clamp



3/16mm, 6mm Allen Keys

All rights reserved.

No part of this document may be reproduced, stored in a retrieval system, or transmitted by any form or by any means, electronic, mechanical, photo-copying, recording, or otherwise, except as may be expressly permitted by the applicable copyright statutes or in writing by the Publisher.

Trailer Hitch Setup

- Remove the pipe clamp bolt attached to the trailer hitch with a 6mm Allen key.



- After removing the pipe clamp, you can change its place according to your requirement.



- Tighten it properly with a 6mm Allen key.



- Change the position of another pipe clamp according to your requirement using the previous procedure.



- Align the pipe clamps according to your setup needs, as shown in the images.



YOUR PROAIM TRAILER HITCH ADAPTER/TOW BAR ALL DRESSED UP AND READY TO GO!



(SHOWN WITH OPTIONAL ACCESSORIES)

Warranty: We offer one year warranty for our products from date of purchase. Within this period of time, we will repair it without charge for labor or parts. Warranty doesn't cover transportation costs nor does it cover a product subjected to misuse or accidental damage. Warranty repairs are subjected to inspection and evaluation by us.

Liability: We are not liable for damage caused by products that we do not supply or from mishandling in transit, accident, misuse, neglect, lack of care of the product, or service by anyone other than our company.

Contact Us: In case of any kind of dissatisfaction, please Contact us immediately and we promise our utmost support and care until you use our product.