PR → A | M Tri-Way Damper System (VI-TRIW-00)

Assembly Manual



What's In The Box

Please inspect the contents of your shipped package to ensure you have received everything that is listed below.







All rights reserved.

No part of this document may be reproduced, stored in a retrieval system, or transmitted by any form or by any means, electronic, mechanical, photo-copying, recording, or otherwise, except as may be expressly permitted by the applicable copyright statutes or in writing by the Publisher.

Tri-Way Damper System Setup

 Attach the Tri-way Damper with L-plate (not included) or your Mounting plate. There are several threaded holes on the L-plate for attachment of the Tri-way Damper.





 Now match the holes of the Tri-way Damper with L-plate. Now insert the bolt and tighten it properly with 5/16 Allen key, as shown in the image.





 You can set the front damping adjustment by rotating the top knob.





 Similarly, you can set the Left & Right damping adjustments by rotating the knobs marked in the image.





• Loosen the knob to attach the Camera Gimbal setup with it.





YOUR PROAIM TRI-WAY DAMPER SYSTEM ALL DRESSED UP AND READY TO GO!



(SHOWN WITH OPTIONAL ACCESSORIES)

Warranty: We offer one year warranty for our products from date of purchase. Within this period of time, we will repair it without charge for labor or parts. Warranty doesn't cover transportation costs nor does it cover a product subjected to misuse or accidental damage. Warranty repairs are subjected to inspection and evaluation by us.

Liability: We are not liable for damage caused by products that we do not supply or from mishandling in transit, accident, misuse, neglect, lack of care of the product, or service by anyone other than our company.

Contact Us: In case of any kind of dissatisfaction, please Contact us immediately and we promise our utmost support and care until you use our product.