

FULLPRO

FULLER PROFESSIONAL

APPEARANCE®

Floor Finish



WARNING

See right panel for precautions and first aid.

Net Contents: 55 Gallons (208L)

APPEARANCE® Floor Finish

Product No.: 96355

APPEARANCE® is a new generation floor finish that achieves maximum performance when maintained by spray buffing and/or high speed buffing. APPEARANCE® has a unique combination of polymers and synthetic waxes that respond well to buffing, yet have superior resistance to scuffing, scratching and marking. The beautiful shine that will last and last.

INITIAL APPLICATION



MAINTENANCE



DIRECTIONS FOR FLOOR CLEANING

INITIAL APPLICATION

1. **REMOVE** old sealer/finish using a Fullpro stripper and following label directions.
2. **APPLY** a thin coat of **Appearance®** using a clean finish mop.
3. **DRY**: Allow 20-30 minutes drying time.
4. **APPLY** 4 coats for best results allowing for adequate drying time between each coat.

MAINTENANCE

1. **DUST MOP**, damp mop or sweep regularly.
2. **SPRAY** onto a 4' x 6' area using a fine to medium spray.
3. **BUFF** as needed using high speed machine and appropriate pad.

Note: Clean and recoat areas as the foundation becomes thin or as buffing response decreases.

FOR INDUSTRIAL USE ONLY

IMPORTANT: Use only as directed. Do not mix with anything unless recommended since harmful conditions and poor performance could result. Do not pour unused product back into original container. All floors are slippery when wet. To prevent falls, exercise care when working and block off traffic with "Caution" signs until floor is completely dry.

KEEP OUT OF REACH OF CHILDREN

WARNING

May cause skin irritation. Direct contact with eyes may cause temporary irritation.

Prevention

Observe good industrial hygiene practices.

Response

Wash hands after handling.

Storage

Store away from incompatible materials.

Disposal

Dispose of waste and residues in accordance with local authority requirements.

INSTRUCCIONES PARA LIMPIAR EL PISO

PRIMERA APLICACIÓN

1. **QUITE** el anterior sellador/acabado, usando un raspador Fullpro adecuado, siguiendo las instrucciones de la etiqueta.
2. **APLIQUE** una capa fina de **Appearance®**, usando un trapeador fino, limpio.
3. **SECADO:** Déjelo secar durante 20-30 minutos.
4. **PARA MEJORES** resultados, aplique 4 manos, dejando entre una y otra capa, tiempo suficiente para secar.

MANTENIMIENTO

1. **LA FREGON** a del polvo, fregona húmeda o barre regularmente.
2. **ROCIE** en un 4' X 6' área que utiliza una multa al rocío medio.
3. **DÉ BRILLO** utilizar como necesitado máquina de alta velocidad y apropie almohadilla.

La nota: Limpie y áreas de recoat como la base llega a ser delgada o dando brillo como las disminuciones de la respuesta.

SOLO PARA USO INDUSTRIAL

IMPORTANTE: Sólo usar según lo indicado. No mezclar con nada que no esté recomendado ya que podría resultar en condiciones perjudiciales y rendimiento pobre. No verter el producto no utilizado en el recipiente original. Todos los pisos son resbaladizos cuando están majados. Para prevenir caídas, ejercer precaución al trabajar y bloquear el paso con carteles de "Precaución" hasta que el piso esté completamente seco


MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.

INGREDIENTS/INGREDIENTES: Water/Agua (7732-18-5), Styrene acrylate polymer/Polímero de acrylate de estireno (25085-34-1), Diethylene glycol monoethyl ether/Eter de monoethyl de glicol de Diethylene (111-90-0), Ethylene copolymer/ Copolymer de etileno (67892-91-5), Tri-butoxyethyl phosphate/Fosfato de Tri-butoxyethyl (78-51-3), Styrene acrylic copolymer/El estireno copolymer acrílico (Mixture/Mezcla).

Fuller Commercial Products

One Fuller Way
Great Bend, KS 67530
United States

CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com



96355-1118