

# Accolade™

## SEALER/FINISH

### PRODUCT DESCRIPTION:

Accolade™ is a versatile sealer/finish which has been formulated to protect a wide variety of non-resilient and resilient flooring materials. By blending acrylic polymer elements fortified with urethane, Franklin has combined the properties of a top quality sealer with those of a superior floor finish.

### FEATURES:

#### Versatility:

Accolade™ simplifies floor care by providing effective sealing of porous/old floors and providing an above average gloss with a single product.

#### Exceptional Gloss:

Accolade's™ improved urethane formula provides "finish" like gloss and depth compared to traditional sealer/finish formulas.

#### Repairable:

Accolade™ will stand up to high speed burnishing and frequent detergent scrubbing.

#### Clear Film:

Accolade™ dries to a clear film and is specifically formulated to not yellow over time.

### PRODUCT SPECIFICATIONS:

pH	.....	8.6 ± 0.2
Appearance	.....	Opaque White Emulsion
Fragrance	.....	Polymeric
Freezing Point	.....	About 32°F
% Non-Volatile Solids	.....	19.5 ± 0.5
% Total Solids	.....	25.4
Boiling Point	.....	212°F
Solubility in Water	.....	Dispersible
Flash Point	.....	None
Coverage	.....	1700 to 2000 sq. ft. per gallon (may vary due to differences in porosity of the surface)

**Slip Resistance:** Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM D2047-82.

### INGREDIENTS:

Water	.....	7732-18-5
Styrene acrylic polymer	.....	25085-34-1
Diethylene glycol monoethyl ether	.....	111-90-0
Polypropylene emulsion	.....	Mixture
Tri-butoxyethyl phosphate	.....	78-51-3

DILUTIONS	HEALTH	FLAMMABILITY	REACTIVITY
CONCENTRATE	NFPA 1	NFPA 0	NFPA 0
CONCENTRAR	HMS 1	HMS 0	HMS 0
PROPORCIÓN	SALUD	INFLAMABILIDAD	REACTIVIDAD

0	1	2	3	4
Minimal	Slight	Moderate	Serious	Severe
Minimo	Minimo	Moderar	Grave	Drastico

DATA TECH SHEET


# Accolade™ SEALER/FINISH

# DIRECTIONS

## USE INFORMATION

Before applying **Accolade™** remove old finish and sealer from floor using appropriate Franklin stripper and following label directions. Can be used on terrazzo, quarry tile, brick, unglazed ceramic, Mexican tile, slate, unpolished marble and all types of resilient flooring.

### INITIAL APPLICATION




CAUTION



1. REMOVE



2. APPLY




3. DRY  
30-60




4. APPLY

### MAINTENANCE



1. DUST MOP



2. MOP

## INITIAL APPLICATION

1. **REMOVE** old sealer/finish following label directions using an appropriate Franklin stripper.
2. **APPLY** a thin coat of **Accolade™** using a clean finish mop.
3. **DRY:** Allow 30-60 minutes drying time.
4. **APPLY** 3-4 additional coats. For best results allow adequate drying time between coats.

## MAINTENANCE

1. **DUST MOP** the floor. Remove gum, labels and other attached soils with a long-handled scraper or putty knife.
2. **DAMP MOP OR AUTOSCRUB** using a Franklin cleaner, following the label directions.

**WARNING:** May cause eye, skin and respiratory tract irritation.

### Hazard Statement

Harmful to aquatic life.

### Precautionary Statement

Avoid release to the environment.

### Response

Wash hands after handling.

### Storage

Store away from incompatible materials.

### Disposal

Dispose of contents / container in accordance with local / regional / national / international regulations.

**KEEP OUT OF REACH OF CHILDREN.**

### PERSONAL PROTECTION:

**Respiratory Protection:** Not needed in normal use of this product.

**Ventilation:** Use with adequate ventilation.

**Eye Protection:** Safety glasses are optional.

**Protective Gloves:** Protective gloves are optional.

**Other Protective Clothing or Equipment:** Wear clothing as necessary to prevent skin contact.

### TRANSPORTATION INFORMATION:

**U.S. DOT - Proper Shipping Name:** Not regulated by DOT.

**Marine Pollutant:** No

© FULLER COMMERCIAL PRODUCTS - 2014

One Fuller Way  
Great Bend, KS 67530  
United States  
www.fullercommercial.com

Customer Service (800) 848-4901  
CHEMTREC (800) 424-9300  
Emergency (620) 792-1711  
24 Hour Emergency (800) 424-9300

F1390TDS-0714