



Restorit®

UHS MAINTAINER / SPRAY BUFF

PRODUCT DESCRIPTION:

Restorit® is a multi-purpose floor finish maintainer designed for high speed maintenance programs. It may be used with a mop and bucket, with an autoscrubber, or as a spray buff. **Restorit®** rejuvenates the finish to produce the wet look and prolongs the life of your finish.

FEATURES:

Maintains A Wet Look Gloss:
Prolongs the finish's life when applied regularly after cleaning.

Easy To Apply:
The finish is restored as easy as damp mopping, autoscrubbing, or spray buff application.

Multiple Use:

Use as a mop-on restorer as a cleaner in the autoscrubber, or as a spray buff.

“Pops” The Gloss:

The finish gleams after high speed buffing.

PRODUCT SPECIFICATIONS:

pH (concentrate)	9.5 ± 0.5
Appearance	Milky Light Green
Fragrance	Polymeric
Solids	7.3 ± 0.2
Freezing Point	About 32°F
Solubility in Water	Complete
Flash Point	None
Coverage	4,000 to 20,000 sq. ft. per gallon

Slip Resistance: Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM D2047-82.

INGREDIENTS:

Water	7732-18-5
Acrylate copolymer	25987-66-0
Diethylene glycol monoethyl ether . . .	111-90-0
Modified melamine resin	68002-20-0
Ethylene glycol	107-21-1

DILUTIONS	HEALTH	FLAMMABILITY	REACTIVITY
CONCENTRATE CONCENTRAR	NFPA 0 HMIS	NFPA 0 HMIS	NFPA 0 HMIS
(1:4 RATIO) (1:4 RAZON)	NFPA 0 HMIS	NFPA 0 HMIS	NFPA 0 HMIS
(1:8 RATIO) (1:8 RAZON)	NFPA 0 HMIS	NFPA 0 HMIS	NFPA 0 HMIS
PROPORCIÓN	SALUD	INFLAMABILIDAD	REACTIVIDAD

0	1	2	3	4
Minimal	Slight	Moderate	Serious	Severe
Mínimo	Mínimo	Moderar	Grave	Drástico

DATA SHEET

Restorit® UHS MAINTAINER / SPRAY BUFF

DIRECTIONS

USE INFORMATION:

Always dust mop floor first. Remove gum, labels and other attached soil deposits with a putty knife or long handled scraper. For best results preclean the floor with Franklin Compare.


AUTOSCRUB APPLICATION



MOP-ON APPLICATION



SPRAY BUFF



AUTOSCRUB APPLICATION

1. **DILUTE Restorit®** at 6 ounces per gallon (1:20 ratio) of cool water in the solution tank.
2. **AUTOSCRUB:** Apply solution and scrub with a red or white pad. Squeegee up excess solution from the floor and allow to dry thoroughly.
3. **BURNISH** as desired to "pop-the-gloss".

MOP-ON APPLICATION

1. **DILUTE Restorit®** at 32 ounces per gallon (1:4 ratio) of cool water.
2. **APPLY** solution with a clean mop. Change solution when it becomes dirty. No rinsing required. Allow to dry thoroughly.
3. **BURNISH** as desired to "pop-the-gloss".

SPRAY BUFF APPLICATION

1. **SPRAY** undiluted product onto a 4' x 6' area using a fine to medium spray. If using ultra high-speed equipment, spray sparingly in front of machine.
2. **BUFF** to a shine using a low speed rotary machine with a red or white polishing pad. With ultra high-speed equipment, use an appropriate burnishing pad.

WARNING

May cause mild eye and skin irritation. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Prevention

Avoid release to the environment.

Response

Wash hands after handling.

Storage

Store away from incompatible materials.

Disposal

Dispose of contents/container in accordance with local / regional / national / international regulations.

KEEP OUT OF REACH OF CHILDREN.

Franklin Cleaning Technology

One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com

PERSONAL PROTECTION:

Respiratory Protection: Not needed under normal conditions.

Ventilation: Use with adequate ventilation.

Eye Protection: Safety glasses are optional.

Protective Gloves: Safety gloves are optional.

Other Protective Clothing or

Equipment: Wear clothing as necessary to prevent skin contact.

TRANSPORTATION

INFORMATION:

U.S. DOT - Proper Shipping Name: Not Regulated by DOT.

Marine Pollutant: No