

DANGER

Harmful if swallowed. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Prevention

Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves. Wear eye / face protection.

Response

If swallowed: Rinse mouth. Do NOT induce vomiting. **If on skin:** Wash with plenty of water. **If inhaled:** Remove person to fresh air and keep comfortable for breathing. **If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/ doctor. Specific treatment (see SDS). **If skin irritation occurs:** Get medical advice / attention. Take off contaminated clothing and wash before reuse. Collect spillage.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Dispose of contents / container in accordance with local / regional / national / international regulations.



One Gallon (3.78L)

Protect From Freezing



OFFENSE™
PATENTED, FAST ACTING, NO-RINSE STRIPPER

DANGER

See side panel for important safety precautions and first aid.

INGREDIENTS/INGREDIENTES

CAS#

Water/Agua.....7732-18-5
Ethylene glycol phenyl ether/
Etilenglicol fenil éter.....122-99-6
Monoethanolamine/Monoetanolamina.....141-43-5
2-Butoxyethanol/2-Butoxiolanol.....111-76-2
Sodium 1-Octane Sulfonate.....5324-84-5



00785990218016



Franklin Cleaning Technology


One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com

OFFENSE™ Patented, Fast acting, No-rinse stripper

Product # **F218022**

OFFENSE™ is a highly active, low foam stripper that quickly penetrates and effectively dissolves multiple layers of floor finish build-up for easy, rinse-free removal. For use on vinyl, vinyl composition, vinyl asbestos, asphalt, marble, terrazzo, concrete and magnesite surfaces.

FLOOR STRIPPING



DIRECTIONS FOR USE

Before Stripping always dust mop the floor and remove gum, labels and other attached soil deposits with a long handled scraper or utility knife.

MOP ON - MOP OFF

- MIX:** Dilute at 21 ounces per gallon (1:6 ratio) of cool water for normal buildup or 32 ounces per gallon (1:4 ratio) of cool water for extreme build up.
- MOP** the diluted solution of OFFENSE™ onto the floor. Let stand for 4-5 minutes, then agitate with the same mop. Do not allow solution to dry.
- REMOVE** the remaining solution off the floor using a mop or wet vacuum.
- REPEAT** steps two and three if any finish remains on floor. Rinsing may be required for dilutions stronger than 1:4.

SPECIAL PRECAUTIONS: Use caution as floors become very slippery. Must be diluted. Not for use on wood or painted surfaces. Not for use on linoleum or rubber floors or daily maintenance of resilient floors. Before use on asphalt tile, test a small hidden area for any color change. Use in adequate ventilation.

FOR INDUSTRIAL USE ONLY.

IMPORTANT: Use only as directed. Do not mix with anything unless recommended since harmful conditions and poor performance could result. Do not pour unused product back into original container. All floors are slippery when wet. To prevent falls, exercise care when working and block off traffic with "Danger" signs until floor is completely dry.

KEEP OUT OF REACH OF CHILDREN

INSTRUCCIONES PARA SU USO

Antes de eliminar pasar siempre un estropajo seco por el piso y quitar goma de mascar, rótulos y demás depósitos sucios con un rascador de manija larga o una espátula para masilla.

PONER Y SACAR CON ESTROPAJO

- MEZCLAR:** Diluir a 21 onzas por galón (1:6 ratio) de agua fría de acumulación normales o 32 oz por galón (1:4 ratio) de agua fresca para la acumulación extrema de hasta.
- PASAR** la solución diluida de OFFENSE™ por el piso con un estropajo. Dejar estar 4 a 5 minutos y luego agitar con el mismo estropajo. No permitir que la solución se seque.
- QUITAR** la solución restante del piso utilizando un estropajo o aspiración húmeda.
- REPETIR** los pasos dos y tres si queda acabado en el piso. Tal vez haga falta enjuagar con diluciones más fuertes que 1:4.

PRECAUCIONES ESPECIALES: Ejercer precaución ya que los pisos se vuelven muy resbaladizos. Debe diluirse. No es para uso en superficies de madera o pintadas. No es para uso en pisos de linóleo o caucho ni para el mantenimiento diario de pisos flexibles. Antes de utilizarse en tejas de asfalto deberá probarse una pequeña área escondida por cambios de color. Utilizar con ventilación adecuada.

ÚNICAMENTE PARA USO INDUSTRIAL

IMPORTANTE: Sólo usar según lo indicado. No mezclar con nada que no esté recomendado ya que podría resultar en condiciones perjudiciales y rendimiento pobre. No verter el producto no utilizado en el recipiente original. Todos los pisos son resbaladizos cuando están majados. Para prevenir caídas, ejercer precaución al trabajar y bloquear el paso con carteles de "Peligro" hasta que el piso esté completamente seco.

MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS

F218022-0914