

Super Gard™

UNDERCOATER SEALER

PRODUCT DESCRIPTION:

Super Gard™ represents a "modern concept" in acrylized emulsion polymer chemistry. It is a major breakthrough in reference to the total undercoater/sealer protection of all resilient and non-resilient floors, with the exception of unsealed wood floors. **Super Gard™** is formulated with metalized acrylic polymers, thereby achieving exceptional levels of durability and protection. **Super Gard™** is an excellent choice where protection from salt exposure is required.

FEATURES:

Super Protective Coating:

Super Gard™ is salt resistant and has outstanding black heel mark and scuff resistance properties.

Exceptional Stain Resistance:

Super Gard™ prevents stains from setting into the floor. The floor is protected from oil, rust, betadine and other soils.

Non-Yellowing:

Super Gard™ is a water-based system with no waxes or resins to cause darkening or yellowing.

Easy and Economical:

No foaming or streaking even under high humidity conditions. Increases the coverage of top coating.

PRODUCT SPECIFICATIONS:

pH	8.8 ± 0.5
Appearance	White Emulsion
Fragrance	Polymeric
Freezing Point	About 32°F
% Total Solids	21.1
% Non-Volatile Solids	16.3
Boiling Point	212°F
Solubility in Water	Complete
Flash Point	None
Coverage	1700 to 2000 sq. ft. per gallon (may vary due to differences in porosity of the surface)

Slip Resistance: Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM D2047-82.

INGREDIENTS:

Water	7732-18-5
Acrylate copolymer	28263-96-9
Ethylene glycol	107-21-1
Diethylene glycol monoethyl ether	111-90-0
Tri butoxyethyl phosphate	78-51-3

DILUTIONS	HEALTH	FLAMMABILITY	REACTIVITY
CONCENTRATE	NFPA 0	HMIS 0	NFPA 0
CONCENTRAR			
PROPORCIÓN	SALUD	INFLAMABILIDAD	REACTIVIDAD

0	1	2	3	4
Minimal	Slight	Moderate	Serious	Severe
Mínimo	Mínimo	Moderar	Grave	Drástico

DATA SHEET


Super Gard™ UNDERCOATER/SEALER

DIRECTIONS


USE INFORMATION

Super Gard™ is recommended for use on vinyl composition, vinyl asbestos, vinyl, asphalt, linoleum and rubber floors. May be used on nonresilient surfaces that are not glazed. These surfaces include concrete, terrazzo, quarry tile, Mexican tile, brick, marble, slate and other nonresilient floors.

INITIAL APPLICATION



CAUTION




1. REMOVE



2. APPLY




3. DRY



4. FINISH

MAINTENANCE



1. DUST MOP



2. MOP

INITIAL APPLICATION

1. **REMOVE** old sealer or finish using a Franklin stripper and following label directions.
2. **APPLY** one or two coats of **Super Gard™** using a clean finish mop and a bucket.
3. **DRY:** For best results allow adequate drying time between each coat.
4. **FINISH:** Apply 2-3 additional coats of a Franklin floor finish. For best results allow adequate drying time between each coat.

MAINTENANCE

1. **DUST MOP** the floor. Remove gum, labels and other attached soil deposits with a long handled scraper or putty knife.
2. **DAMP MOP OR AUTOSCRUB** using a Franklin cleaner and following the label directions.

WARNING

May cause mild eye and skin irritation.

Prevention

Observe good industrial hygiene practices.

Response

Wash hands after handling.

Storage

Store away from incompatible materials.

Disposal

Dispose of waste and residues in accordance with local authority requirements.

Franklin Cleaning Technology

One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com

PERSONAL PROTECTION:

Respiratory Protection: Not needed in normal use of this product.

Ventilation: Use with adequate ventilation.

Eye Protection: Safety glasses are optional.

Protective Gloves: Protective gloves are optional.

Other Protective Clothing or

Equipment: Wear clothing as necessary to prevent skin contact.

TRANSPORTATION

INFORMATION:

U.S. DOT - Proper Shipping Name: Not regulated by DOT.
Marine Pollutant: No