

WARNING

Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Prevention

Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves. Wear eye / face protection.

Response


If on skin: Wash with plenty of water. 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see SDS). If skin irritation occurs: Get medical advice / attention. If eye irritation persists: Get medical advice / attention. Take off contaminated clothing and wash before reuse.

Storage


Store away from incompatible materials.

Disposal

Dispose of contents/container in accordance with local / regional / national / international regulations.



FRANKLIN
CLEANING TECHNOLOGY



Water Extraction Carpet Cleaner

Concentrated Extraction Cleaner



WARNING

See side panel for precautions and first aid.

ONE GALLON (3.79L)

Protect From Freezing

INGREDIENTS/INGREDIENTES

Water/Agua	7732-18-5
Tetrapotassium pyrophosphate/ Pirofosfato tetrapotasio	7320-34-5
2-Butoxyethanol/ 2-Butoxietanol	111-76-2
Octenylsuccinic Acid/Ácido octenilsuccínico	28805-58-5
Sodium silicate/Silicato de sodio	1344-09-8
Dipropylene glycol monomethyl ether/Eter de monomethyl de glicol de Dipropylene	34590-94-8

CAS#



00785990534017

Franklin Cleaning Technology


One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com



Water Extraction Carpet Cleaner Concentrated Extraction Cleaner Product# **F534022**

Water Extraction Carpet Cleaner is formulated for hot water extraction systems and provides an aggressive combination of ingredients for cleaning carpets that are loaded with tough soils. Designed for use where the soil load is the carpet's worst enemy. These environments often include schools, restaurants and industrial offices.

EXTRACTION



1. DILUTE 2. EXTRACT 3. FORCE DRY

DIRECTIONS FOR USE

Always thoroughly vacuum the carpet and remove any attached deposits from the carpet prior to use. If there is a question on colorfastness, always pretest in an inconspicuous area.

EXTRACTION

- DILUTE** at 1 ounce per gallon (1:128 ratio) of hot water. Use 2 ounces per gallon (1:64) of hot water on extreme soil conditions. For best results on traffic lanes, prespray with **Answer™ Carpet Cleaner** following label directions.
- EXTRACT.**
- FORCE DRY** using carpet dryers or fans.

FOR INDUSTRIAL USE ONLY

IMPORTANT: Use only as directed. Do not mix with anything unless recommended since harmful conditions and poor performance could result. Do not pour unused product back into original container. All floors are slippery when wet. To prevent falls, exercise care when working and block off traffic with "Caution" signs until floor is completely dry.

KEEP OUT OF REACH OF CHILDREN

INSTRUCCIONES PARA USAR

Aspirar siempre la alfombra a fondo y quitar todo depósito que se haya acumulado en la misma antes de usar. Si hay alguna duda acerca de la firmeza del color de la alfombra, realizar siempre una prueba en un lugar poco visible.

EXTRACCIÓN

- DILUIR** en una proporción de 1 onza por galón (razón de 1:128) de agua caliente. Para las áreas extremadamente sucias diluir 2 onzas en agua caliente (1:64). Para mejor resultado en las áreas de mayor tráfico, pre-rocíar con **Answer™ Limpiador de alfombras** siguiendo las instrucciones en la etiqueta.
- EXTRAER.**
- SECAR MECÁNICAMENTE** usando secadores de alfombra o ventiladores.

ÚNICAMENTE PARA USO INDUSTRIAL

IMPORTANTE: Sólo usar según lo indicado. No mezclar con nada que no esté recomendado ya que podría resultar en condiciones perjudiciales y rendimiento pobre. No verter el producto no utilizado en el recipiente original. Todos los pisos son resbaladizos cuando están mojados. Para prevenir caídas, ejercer precaución al trabajar y bloquear el paso con carteles de "Precaución" hasta que el piso esté completamente seco.

MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS