











检测报告

TEST REPORT

报告编号:

REPORT NO.:

25201803544

样品名称:

瓷质砖

NAME OF SAMPLE:

PORCELAIN TILE

委托单位:

河源市罗曼缔克实业有限公司

APPLICANT: HEYUAN ROMANTIC CERAMICS CO. LTD

检验日期:

DATE OF TEST:

13/08/2018 - 22/08/2018 (dd/mm/yy)

国家建筑卫生陶瓷检测重点实验室 STATE KEY TESTING LABORATORY OF BUILDING CERAMICS AND SANITARY WARE 佛山出入境检验检疫局检验检疫综合技术中心 INSPECTION AND QUARANTINE COMPREHENSIVE TECHNOLOGY CENTRE OF FOSHAN ENTRY-EXIT INSPECTION & QUARANTINE BUREAU

INSPECTION AND QUARANTINE COMPREHENSIVE TECHNOLOGY CENTRE OF FOSHAN ENTRY-EXIT INSPECTION & QUARANTINE BUREAU

检测报告

TEST REPORT

报告编号: Report No:

检验负责人

Tested by

杨鹏

25201803544

共5页 第 2 页

Page 2 of 5

样品名称 Name of sample	瓷质砖 PORCELAIN TILE	名义尺寸 Nominal size (N)	90cm×90cm	
表面特性 Nature of the surface	有釉 Glazed (GL)	工作尺寸 Work size	900mm×900mm×10.6mm	
类别 Group	ВІа	预期用途 Intended use	室内外墙地砖 Floorings and wall finishes, Interior and exterior	
样品标记 Mark of samples	MZ300C	样品数量 Quantity of sample	30 块 30 Pieces	
委托单位 Applicant	河源市罗曼缔克实业有限公司 HEYUAN ROMANTIC CERAMICS CO. LTD	委托单位地址 Address of applican	广东省佛山市禅城 区石湾镇东风路 15 号 NO.15 OF DONGFENG ROAD,SHIWAN,FOSHAN, GUANGDONG,CHINA	
委托单位电话 Telephone of applicant	86-18688803709	委托单位传真 Fax of Applicant	86-757-83051096	
样品来源 Source of Samples	委托单位自送样品 Samples selected by applicant	接样日期 Received on	09/08/2018	
检验依据 Test Standard	verification of constancy of per	formance and marking	ith low water absorption of Group BIs	
检验结论 Conclusion of Test	样品经检验,所检验项目的检验	d结果符合 EN 14411:2 equirement of Annex	016 标准中附录 G 的规定。 G of standard EN 14411:2016 with	
检验单位盖章 Stamp of Test Unit	日期: 27/08/2018 Date:	检验单位联系方式 Address of Test Unit	地址: 广东省佛山市禅城区魁奇一路濮石(国际) 金属交易中心十八座二楼 Address: 2/F, Building 18, Lanshi International Metal Exchange Center Kuiqiyi Road, Chancheng District Foshan, Guangdong, China (528000) 电话 (Tel): 86-757-83960558 86-757-83827991 传真 (Fax): 86-757-83827971 邮箱 (E-mail): fsiqtc@163.com 网址 (url): http://www.fsiqtc.com/	
声明 Notes	1、我们已尽所知所能实施上述检验, All inspections are carried out This report does not in any respect abso 2、未经本实验室书面许可,不得能	conscientiously to the olve the other related parties 邓分复制本报告; cept in full, without the prior	关各方根据合同和法律所承担的责任和义务; best of our knowledge and ability from his contractual and legal obligations. written approval from the issuing laboratory.	

Inspected by

Approved by 7 3.12

INSPECTION AND QUARANTINE COMPREHENSIVE TECHNOLOGY CENTRE OF FOSHAN ENTRY-EXIT INSPECTION & QUARANTINE BUREAU

检测报告 TEST REPORT

报告编号: Report No:

25201803544

共5页第3页

Page 3 of 5

委托单位声明 Remark of applicant

产品系列名称:瓷质砖

Product family:PORCELAIN TILE

表面特性:凹凸面,有釉

Nature of the surface: Rough, Glazed (GL)

产品类别 Group:B I a

名义尺寸 Nominal size (N):90cm×90cm

本系列所包含的产品型号 Items in the family:

MZ100C, MZ300C, MZ400C, MZ500C, MZ100C-D1, MZ100C-D2, MZ001CP, MZ101CP, MZ301CP, MZ501CP, MZ601CP, MZ701CP, MZ801CP, MZ901CP, MZ121, MZ221

本系列所包含产品型号的吸水率、规格、使用的材料、采用的成型方法以及表面特征是一致的,区别在于外观

All items in the family are same in water absorption, dimensions and thickness, material, method of manufacture and natural of surface except for the design of appearance.

样品照片 Photo of Samples





INSPECTION AND QUARANTINE COMPREHENSIVE TECHNOLOGY CENTRE OF FOSHAN ENTRY-EXIT INSPECTION & QUARANTINE BUREAU

检测报告 TEST REPORT

报告编号:

25201803544

Report No:

共5页 第 4 页

Page 4 of 5

EN 14411:2016 Ceramic tiles - Definition, classification, characteristics, assessment and verification of constancy of performance and marking Annex G Requirements for dry-pressed ceramic tiles with low water absorption of Group BIa $(E_b \le 0.5 \%)$

条款 Clause	性能 Properties	检验方法 Test Method	要求 Requirements	检验结果 Results	判定 Verdict			
A	尺寸和表面质量 Dimensions and surface quality							
A.1	长度和宽度 Length and Width 每块砖的平均尺寸相对于工作尺寸的	10545-2:1997	±0.6%	-0.01%~+0.01%	P			
A.I	允许偏差 The permissible deviation of the average size for each tile (4 sides) from the work size		±2.0mm	-0.1mm~+0.1mm	P			
A.2	厚度 Thickness 每块砖厚度的平均值相对于工作尺寸的最大允许偏差	EN ISO 10545-2:1997	±5%	-0.7%~+1.0%	P			
	The permissible deviation, of the average thickness of each tile from the work size thickness		±0.5mm	-0.1mm~+0.1mm	P			
В	物理性能 Physical properties							
B.1	吸水率 质量分数 Water absorption Percent mass fraction	EN ISO 10545-3:2018	<i>E</i> _b ≤0.5%	0.06%	P			
			单个值不大于 0.6% Individual maximum 0.6%	0.05%~0.07%	P			
B.2	破坏强度/N Breaking strength, in N	EN ISO 10545-4:2014	≥1300	2742	P			
В.3	断裂模数/(MPa) Modulus of rupture, in MPa 不适用于破坏强度≥ 3000N 的陶瓷砖 Not applicable to tiles with breaking strength≥ 3000N	EN ISO 10545-4:2014	平均值≥35 Minimum 35	41.8	P			
			单个值≥32 Individual minimum 32	39.7~44.2	P			
B.4	耐磨性 Abrasion resistance	EN ISO 10545-7:1998	报告耐磨级别 Report abrasion class	4级 Class 4	Or - 1			
	用于地面的有釉砖的表面耐磨性 Resistance to surface abrasion of glazed tiles intended for use on floors		报告耐磨转数 Report cycles passed	2100	25/2			
B.6	抗热震性 Thermal shock resistance	EN ISO 10545-9:2013	应通过此项测试 Pass	样品经试验,无炸 裂或裂纹 Fully resistance	P			
B.7	抗釉裂性: 有釉砖 Crazing resistance: glazed tiles	EN ISO 10545-11:1996	应通过此项测试 Pass	样品经试验,无裂 纹或剥落 Fully resistance	P			
B.8	抗冻性 Frost resistance	EN ISO 10545-12:1997	应通过此项测试 Pass	所有样品无裂纹或 破损 Fully resistance	P			
B.9	防滑性能	DIN 51130:2014	报告检验结果 Declared value	α ges:6.6°	1000			
	Slipperiness			类别 Classification: R9	30, -10			

INSPECTION AND QUARANTINE COMPREHENSIVE TECHNOLOGY CENTRE OF FOSHAN ENTRY-EXIT INSPECTION & QUARANTINE BUREAU

检测报告 TEST REPORT

报告编号:

25201803544

第 5 页 共5页

Page 5 of 5

Report No:

EN 14411:2016 Ceramic tiles - Definition, classification, characteristics, assessment and verification of constancy of performance and marking Annex G Requirements for dry-pressed ceramic tiles with low water absorption of Group BIa ($E_b \le 0.5\%$)

条款 Clause	性能 Properties	检验方法 Test Method	要求 Requirements	检验结果 Results	判定 Verdicts				
B.14	防火性能 Reaction to fire	无需测试 CWT	Al or Al _{FL} 级 Class Al or Al _{FL}	墙砖: Al 级 地砖: Al 组 Used for walls: Class Al Used for floorings: Class Al a	of P				
С	化学性能 Chemical properties								
C.1	耐污染性 Resistance to staining								
	a)轻油中的铬绿 a) Green staining agent in light oil	EN ISO 10545-14:2015	不低于 3 级 Minimum Class 3	5级 Class 5	P				
	b)轻油中的红色污染物 b) Red staining agent in light oil	EN ISO 10545-14:2015	不低于 3 级 Minimum Class 3	5级 Class 5	P				
	c) 13g/L 碘酒液 c) Iodine, 13g/L solution in alcohol	EN ISO 10545-14:2015	不低于 3 级 Minimum Class 3	5级 Class 5	P				
	d)橄榄油 d) Olive oil	EN ISO 10545-14:2015	不低于 3 级 Minimum Class 3	5级 Class 5	P				
	Resistance to chemicals 耐家庭化学试剂和游泳池盐类 Resistance to household chemicals and swimming pool salts 家庭化学试剂: 氯化铵溶液,100g/L EN ISO 不低于 B 级								
	a) Household chemicals: Ammonium chloride, 100g/L b) 游泳池盐类: 次氯酸钠溶液, 20mg/L b) Swimming pool salts: Sodium hypochlorite solution, 20mg/L	10545-13:2016 EN ISO 10545-13:2016	Minimum class B 不低于 B 级 Minimum class B	A	P				
	耐低浓度酸和碱 Resistance to low concentrations of acids and alkalis								
	a) 3%盐酸溶液(v/v) a) Hydrochloric acid solution, 3% (v/v)	EN ISO 10545-13:2016	报告检验结果 Declared value	LA	00,00				
	b) 柠檬酸溶液, 100g/L b) Citric acid solution, 100g/L	EN ISO 10545-13:2016	报告检验结果 Declared value	LA .	4 10 TO				
	c) 氢氧化钾溶液, 30g/L c) Potassium hydroxide, 30g/L	EN ISO 10545-13:2016	报告检验结果 Declared value	LA	de la				
	耐高浓度酸和碱 Resistance to high concentrations of acids and alkalis								
	a) 18%盐酸溶液(v/v) a) Hydrochloric acid solution, 18% (v/v)	EN ISO 10545-13:2016	报告检验结果 Declared value	НВ	100 A				
	b) 5 %乳酸溶液(v/v) b) Lactic acid, 5 % (v/v)	EN ISO 10545-13:2016	报告检验结果 Declared value	НА	10 10 10 10 10 10 10 10 10 10 10 10 10 1				
	c) 氢氧化钾溶液, 100g/L c) Potassium hydroxide, 100g/L	EN ISO 10545-13:2016	报告检验结果 Declared value	НВ	100				

用语说明 Possible test case verdicts

1. P(ass): 合格 Test item does meet the requirement.

2. F(ail): 不合格 Test item does not meet the requirement.

3.—: 未进行判定 Verdict was not carried out. 4. N/A: 不适用 Test case does not apply to the test item.

正 本 申 请

X

存

INSPECTION AND QUARANTINE COMPREHENSIVE TECHNOLOGY CENTRE OF FOSHAN ENTRY-EXIT INSPECTION & QUARANTINE BUREAU

CERTIFICATE

Of Conformity

Certificate No:

25201803544

Applicant:

HEYUAN ROMANTIC CERAMICS CO. LTD

Address of Applicant:

NO.15 OF DONGFENG ROAD, SHIWAN, FOSHAN, GUANGDONG CHINA.

Product:

PORCELAIN TILE

Type designation:

MZ100C, MZ300C, MZ400C, MZ500C, MZ100C-D1, MZ100C-D2, MZ001CP, MZ101CP,

MZ301CP, MZ501CP, MZ601CP, MZ701CP, MZ801CP, MZ901CP, MZ121, MZ221

Technical data:

Dry-pressed ceramic tiles for Floorings and wall finishes, Interior and

exterior, with water absorption $E_b \le 0.5\%$, Group B I a, Rough, Glazed,

90cm × 90cm

The submitted samples of the above product have been tested for CE marking according to the following **European Directives:**

(EU)No.305/2011-the Construction Products Regulation

Standard used for showing compliance with the essential requirements in the specified directive:

Standard

Test report

Issued by

Date

EN 14411:2016

25201803544

IQCTC of FSCIQ

Aug.27, 2018

The referred test report shows that the product complies with standard recognized as giving presumption of compliance with the essential requirements in the specified EU Directive.

After preparation of the necessary technical documentation as well as the conformity declaration the CE marking as shown below can be affixed on the product. Other relevant Directives have to be observed.

This certificate is NOT valid for: i) uses in suspended ceilings; ii) uses subject to requirements against accidental fall of objects on to transit areas; iii) uses subject to dangerous substances regulations; iv) uses in vehicular circulation areas.

This document is the property of Inspection and quarantine comprehensive technology centre of Foshan Entry-exit Inspection & Quarantine Bureau, and it is not transferable. Only the applicant may reproduce this certificate.

CE

XIAO JINGHONG Director

Issue Date: Aug.27, 2018 Expiration Date: Aug.26, 2019



Note: This certificate is part of the full report and should be read in conjunction with it.

INSPECTION AND QUARANTINE COMPREHENSIVE TECHNOLOGY CENTRE OF FOSHAN ENTRY-EXIT INSPECTION & QUARANTINE BUREAU 2/F, Building 18, Lanshi International Metal Exchange Center, Kuiqiyi Road, Chancheng District, Foshan, Guangdong, China (528000) TEL: 86-757-83960558 FAX: 86-757-83827971