

Features

- Capable of reaching up to 4,000 revolutions per minute.
- · It has a variety of adapters for tubes of different capacities.
- Maintenance free motor.
- Easy programming access.
- · Automatic sound alert at the end of the programmed operation time.

Applications

Clinical laboratories

 \cdot Cell biology

Blood banks
Molecular biology

Biochemistry

Accessories included

· 12 adapters for 1.5ml / 2ml
· AC / DC adapter

• 12 adapters for 2ml / 3ml / 4ml • 12 adapters for 5ml / 6ml / 7ml • Rotor C-13000 with fixed angle for 12 tubes of 10ml / 15ml

TECHNICAL DATA	
Model	PRO-12M
Speed range	300- 4,000 RPM.
Timer	15 s to 99 min.
Maximum RFC	2,460 g.
Rotor capacity	12 x 1.5 / 2ml / 3ml / 4ml / 5ml / 6ml / 7ml / 10ml / 15ml.
Weight	11 kg / 24.2 lb.
Dimensions	380 x 320 x 180mm / 14.9" x 12.5" x 7.0".
Power supply	110/240V, 50/60 Hz AC adapter.
Warranty	l year



www.velab.net+1 956.429.3410

sales@velab.net

1431 W Polk Ave, Pharr Texas 78577