



VE-2202

VE-4002

VE-6202

► **Features**



- High contrast LCD screen
- Large stainless steel pan
- Leveling feet: Two back feet.
- RS 232 interface
- Capacity tracker
- Multiple weighing units

► **Standard Functions**

- Weighing
- Counting function
- Percentage weighing
- Accumulation function
- Dynamic weighing
- Density determination
- Hold function
- Computing function
- High low limit alarm
- Gross/Net/Tare weight

► **Accessories Included**

- Calibration weight, 1kg (x2)
- RS-232 cable
- Hook for suspended weighing
- Transparent protective cover
- Rechargeable battery
- USB adapter

► **TECHNICAL DATA**

	VE-2202	VE-4002	VE-6202
Model	VE-2202	VE-4002	VE-6202
Capacity	2200 / 3200 g	4000 g	6200 g
Readability	0.01 / 0.05 mg	0.01 g	0.01 g
Repeatability	0.02 / 0.05 mg	0.02 g	0.02 g
Linearity	±0.02 / 0.05 g	±0.03 g	±0.03 g
Weighing Units	g, ct, oz, ozt, dwt, GN, lb, N, dr, tIT, tIS, tIH, T, T/A/R, /A/R, ms, kg, bat, mom, /lb, total 20 units		
Calibration	External CAL		
Pan Size	168 x 168 mm / 6.6" x 6.6"		
Stabilization Time	≤3 seconds.		
Interface	RS232, Can communicate with computer and printer simultaneously		
Display size	LCD, digit height 23 mm / 1"		
Housing	Metal base and ABS plastic.		
Operating Environment	12° to 28°C / 53° to 82°F / Humidity 20% - 80%		
Overall Dimensions	295 x 208 x 88 mm / 11.6" x 8.1" x 3.4"		
Underhook mechanism	Hook included.		
Power Supply	110/240V, 50/60 AC Adapter.		
Net Weight	4.1 kg / 9 lb.		
Warranty	2 years.		