D Series

Zoom System 0.7X, 0.8X, 1X, 1.5X, 2X, 3X, 4X, 4.5X



Main Features

- · Diopter adjustment on both eyepieces.
- · Binocular head with interpupillary distance adjustment .
- · Head inclined at 45 °.
- · Stage with clips.
- \cdot Software for camera operating, capturing photo, video

















- - and digital analysis.



· Stative, robust, reinforced and easy to transport.









- · Zoom adjustment knobs.
- · Interpupillary distance of 55 ~ 75 mm.
- \cdot Integrated digital camera.
- · Lighting with independent intensity adjustment.

Applications

Focus

· Education: Upper grade levels

· Research

· Industrial

Accessories Included

· USB cable · Software · Dust cover

TECHNICAL DATA

Model VE-S5C

Eyepiece WF 10X/20 mm.

Camera 3 MP, integrated.

Objectives 0.7X, 0.8X, 1X, 1.5X, 2X, 3X, 4X, 4.5X (7 to 45 total increases).

Optical System Greenough System, with variable magnification zoom.

Coarse anti-slip.

Stage Interchangeable, translucent white and white / black.

Ilumination Trasmitted and incident LED.

Operating system Windows XP/ Vista/ 7/ 8/ 10 (32 & 64 bit) 225 x 355 x 270 mm/ 8.8" x 13.9" x 10.6". Dimensions

Power Supply CA 110/240, 50/60 Hz.

Warranty 10 years



www.velab.net

+1 956.429.3410

▶ sales@velab.net

▶ 1431 W Polk Ave, Pharr Texas 78577