



### ► Main Features

- Trinocular head, inclined at 45 °.
- Interpupillary distance of 55 ~ 75mm.
- Stable, robust, reinforced and easy to transport.
- Lighting with independent switches.
- Diopter adjustment in both eyepieces.
- Anti-slip ring on lens and cap.
- Stage with clamps.
- Phototube with 23 mm diameter, compatible with VELAB MC, LX series cameras and VE-SCOPEPAD tablet.
- Two interchangeable plates: opaque glass, for transmitted light and double-sided white / black, for incident light.

### ► Applications

- Education
- Industrial
- Research

### ► Accessories Included

- Power cord
- Dust cover

## TECHNICAL DATA

<b>Modelo</b>	<b>VE-S5</b>
<b>Eyepieces</b>	WF 10X/20 mm.
<b>Objectives</b>	Variable Magnification Zoom System 0.7X, 0.8X, 1X, 1.5X, 2X, 3X, 4X, y 4.5X (7 to 45 total increases).
<b>Stage</b>	Interchangeable 60mm / 2.3 " diameter stage, opaque glass and double-sided white / black.
<b>Focus</b>	Coarse anti-slip control knob.
<b>Illumination</b>	Transmitted and incident LED.
<b>Dimensions</b>	225 x 340 x 270 / 8.8" x 13.3" x 10.6".
<b>Power Supply</b>	110/240V, 50/60 Hz AC adapter.
<b>Warranty</b>	10 years