



VE-WD30

VE-WD60

► **Features**



- RS232 interface.
- High contrast LED display
- Industrial rubber feet
- Internal rechargeable battery.
- Auto shut-off
- Robust stainless steel construction

► **Standard Functions**

- Weighing
- Checkweighing
- Dynamic weighing
- Parts counting
- Hold function

► **Accessories Included**

- Power adapter.

► **TECHNICAL DATA**

	VE-WD30	VE-WD60
Model		
Capacity	30 kg / 65 lb	60 kg / 130 lb
Readability	5 g / 0.01 lb	10 g / 0.02 lb
Repeatability	±5 g/±0.0 1lb	±10 g /±0.02 lb
Linearity	±5 g/±0.01 lb	±10 g /±0.02 lb
Weighing Units	Kg, lb	
Calibration	External	
Pan Size	300 x 400 mm / 11.8" x 15.7"	
Stabilization Time	2 seconds	
Interface	RS232	
IP Protection	IP 65	
Display	LCD, digit height 25mm / 1"	
Housing	Stainless steel construction	
Operating Environment	-10° to 40°C / 14° to 104°F	
Overall Dimensions	300 x 460 x 105 mm / 11.8"x18.1"x4.1"	
Power Supply	110/240V, 50/60 Hz AC Adapter and rechargeable battery	
Net Weight	8 kg / 18 lb	
Warranty	1 year	