JUDO PROFI-PLUS 3/4" - 2"

Backwash protective sediment filter manual version



With silver-plated stainless steel filter screen and high-efficiency point rotation system.



Thanks to JUDO QUICKSET-E, installation in

horizontally and vertically running pipes possible.

For drinking water up to 30 °C Operating pressure range 1.5 - 16 bar

Scope of delivery Type JPF+ 3/4" - 11/4": Filter housing made of high-quality plastic PN 16, built-in rotary flange with bayonet connection made of brass with screw, threaded connector in accordance with EN 10226-1; horizontal and vertical installation is possible; silver-plated filter screen made of stainless steel; large handwheel for backwashing based on point rotation system with simultaneous cleaning of the inspection bell.

Scope of delivery Type JPF 1½" - 2": High grade filter housing PN 16; built-in rotary flange made of brass with screw (threaded connector in accordance with EN 10226-1); horizontal and vertical installation is possible; silver-plated filter screen made of stainless steel; large handwheel for backwashing based on point rotation system with simultaneous cleaning of the inspection bell.

Туре	JPF+	JPF+	JPF+	JPF	JPF
Pipe connection	3/4"	1"	1¼"	11/2"	2"
Flow rate m³/h *	6.7	7.6	8.5	18	22
Installation length mm	180	195	230	252	280
Filtration rate micron	100	100	100	100	100
Dimensions W x D x H mm	130 x 165 x 410	130 x 165 x 410	130 x 170 x 410	158 x 207 x 432	158 x 215 x 432
Order number	8010072	8010073	8010074	8010213	8010214

Versions with non-standard mesh sizes (not silver-plated)	JPF+	JPF+	JPF+	JPF	JPF
Pipe connection	3/4"	1"	1¼"	11/2"	2"
Mesh size 30 micron	8010075	8010076	8010077	8015002	8015012
Mesh size 320 micron	8010078	8010079	8010080	8015003	8015013
Mesh size 500 micron	8010081	8010082	8010083	8015004	8015014





* Flow rate for drinking water with cleaned screen at 0.5 bar pressure loss. Lower flow should be assumed for service water and heavily contaminated water. Professional advice required!

** JU-Control app required



Type JPF+ 3/4" - 11/4"



- Quality assured made in Germany
- Reliable protection against particle inflow
- Economical no expensive and complicated cartridge changes
- Uncomplicated easy backwashing
- Efficient effective backwash thanks to point rotation system
- Practical no interruption to the water supply during backwash
- Low impact no waste cartridges and low water consumption thanks to an effective backwash

Installation dimensions see page 82