

- Casing : Plastic
- Material : Plastic
- Operation Power: 1200 W
- High Brightness LED to Increase the Ease and Delight of Use
- Standby: Color Red; Active: Color Blue
- Drying Time: Less than 10-15 seconds
- Drip Proof: IP 23; Isolation: Class 1
- PATENT: USA, EUROPE, CHINA, TAIWAN
- Motor Type: 1HP, 400-750W, 11000-20000 R.P.M., adjustable
- Warm Air Speed Output:65-100 m/s (140-224 mi/hr), adjustable
- Dryer Shall Deliver: 89-124 m3/h (55-76 CFM), adjustable
- Heater Element: ON/OFF heating options. 300-450W, adjustable
- N.W.: 10.8 kg (23.8 lbs); G.W.: 12.8ks (28.2 lbs)
- Unit Size: 322mmW x 624.5mm H x 185mm D [12-43/64" W x 24-19/32"H x 7-9/32"D] (including drain tray)
- Capacity of Drain Tray: 200 cc













EcoMo is the only hand dryer
with BSI issued Carbon Footprint Certification.

Technical Specifications:

- Operating Voltage: 110V-120Vac, 50/60 Hz, 9.2-10 A, 1.0-1.2kW
- Operating Voltage: 220V-240Vac, 50/60 Hz, 9.2-10 A, 1.0-1.2kW
- . Standby Power: Less than 0.5W, Timing Protection: 60 seconds auto shut off
- Circuit Operation: Infrared Automatic, self adjusting
- Motor Thermal Protection: Auto resetting thermostat turns unit off, 120V at 135 Degree C (275 Degree F), 240V at 95 Degree C (221 Degree F).
- Heater Thermal Protection: Auto resetting thermostat turns unit off at 85Degree C(185 Degree F)
- Heater Thermal cut off at 142 dgree C (288 Degree F)
- Sound Level: 76.9 dB at 1 M
- Super Filter Assembly: Antibacterial Filter+Carbon Filter + HEPA Filter
- Ag+ ion (utilize lonpure WPA by Ishizuka Glass Co., Ltd, which received the NSF mark) in the plastic components.
- All plastic 100% recyclable

FEATURES